

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2056
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-7

SUNDRY NOTICES AND REPORTS ON WELLS DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REENTER OR PLUG BACK TO A DIFFERENT RESERVOIR. IT IS APPROPRIATE FOR A PRELIMINARY REPORT ON A WELL FOR SUCH PROPOSALS.		5a. Indicate Type of Lease State ☐ For ☒
1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER		5. State Oil & Gas Lease No.
2. Name of Operator Harvey E. Yates Company		7. Unit Agreement Name
3. Address of Operator P. O. Box 1933, Roswell, New Mexico 88201		8. Form of Lease Name Richardson Fee
4. Location of Well UNIT LETTER R 1980 FEET FROM THE South LINE AND 1980 FEET FROM		9. Well No. 2
10. Well Section 14S RANGE 36E TOWNSHIP 14S		10. Field and Pool, or Without Und. Austin Miss
11. Elevation (Surface or Depth of, RT, GR, etc.) 3963.1 GL		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER ☐	PLUG AND ABANDON ☐ CHANGE PLANS ☐ OTHER ☐	REMEDIAL WORK ☐ COMMENCE DRILLING OPNS. ☐ CASING TEST AND CEMENT JOBS ☒ OTHER ☐	ALTERING CASING ☐ PLUG AND ABANDONMENT ☐ OTHER ☐
--	---	--	--

17. Give a Brief and/or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11/11/82 Depth 13530', Formation-Line. Ran & Cmt'd 5 1/2" Csg as follows:

73 jts	5 1/2"	17#	S-95	LT&C	2931.07
204 jts	5 1/2"	17#	N-80	LT&C	8363.50
36 jts	5 1/2"	17#	S-95	LT&C	1452.44
17 jts	5 1/2"	17#	N-80	Butt	624.66
329 jts	Total Pipe				13371.67

Pkr shoe set @ 13370.5' (Center of pkr rubber) DV tool @ 12,111.50'. Marker jt @ 10441 - 10461' (20.22'). Cmt'd 1st stage w/375 sxs C1 "H" w/.75% Halad 22-A, 0.5% CFR 2, 6# Salt/sx, 1/4# flocele/sx. Plug down @ 6:30 a. m. 11/10/82. Dropped opening bomb & opened DV tool w/1700 psi. Cmt 2nd state w/617 sxs C1 "H" w/0.75% Halad 22-A, 0.5% CFR-2, 6# salt/sx, 1/4# flocele/sx. Dropped closing plug @ 1:00 p.m. Closed DV tool @ 2:05 p. m. w/2600 psi. Set slips. Rel rig @ 5:00 p.m. 11/10/82.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Paul J. Sandoz TITLE Engineer DATE 11/15/82

ORIGINAL SIGNED BY JERRY SEXTON TITLE DISTRICT SUPR. DATE NOV 18 1982

RECEIVED

NOV 17 1982

NOV 17 1982