

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

SEP 3 1982

O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-78

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator
Yates Petroleum Corporation

Address of Operator
207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER I 1980 FEET FROM THE South LINE AND 660 FEET FROM
THE East LINE, SECTION 21 TOWNSHIP 14S RANGE 33E NEPTIL.

15. Elevation (Show whether DF, RT, GR, etc.)
4211.6' GR

5a. Indicate Type of Lease

State ☒ Non ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Date

8. Term of Lease Name

Swan "VB"

9. Well No.

1

10. Field and Pool, or Wildcat

Saunders Permo Penn

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
OIL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPS. ☒
CASING TEST AND CEMENT JOBS ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 17-1/2" hole at 2:45 PM 8-24-82. Set 40' of 20" conductor pipe. Ran 15 joints of 13-3/8" 54# casing set at 450'. 1-Texas Pattern guide shoe at 450'. Insert float at 420'. Cemented w/450 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 4:00 AM 8-25-82. Bumped plug to 800 psi, released pressure and float held okay. Cement circulated 45 sacks to pit. WOC. Drilled out at 4:00 PM 8-25-82. WOC 12 hours. Cut off and welded on flow nipple. Reduced hole to 12-1/4". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Kenneth L. Osborn

TITLE Engineering Secretary

DATE 9-3-82

ORIGINAL SIGNED BY

APPROVED BY JERRY SEXTON

TITLE

DATE

SEP 7 1982

CONDITIONS OF APPROVAL DISTRICT SUPER.

RECEIVED

SEP 7 1982

**O.C.D.
HOBBS OFFICE**