

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State ☒ Fee ☐  
5. State Oil & Gas Lease No.  
LG-814

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name Woodpecker SY State
Address of Operator 207 South 4th St., Artesia, NM 88210	9. Well No. 4
Location of Well UNIT LETTER <u>C</u> <u>B</u> , 660 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 21 TOWNSHIP 14S RANGE 33E NMPM.	10. Field and Pool, or WHdcat Saunders Permo Upper Pen
15. Elevation (Show whether DF, RT, GR, etc.) 4218.6' GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒ OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 17-1/2" hole at 6:30 PM 9-30-82. Ran 12 joints of 13-3/8" 48# K-55 casing set at 450'. 1-Texas Pattern guide shoe at 450'. Insert float at 427'. Cemented w/450 sacks Class "C" 2% CaCl<sub>2</sub>. Compressive strength of cement - 1250 psi in 12 hours. PD 10:45 AM 10-1-82. Bumped plug to 500 psi, released pressure and float held okay. Cement circulated 35 sacks to pit. WOC. Drilled out 11:00 PM 10-1-82. WOC 12 hours and 15 minutes. Cut off and welded on flow nipple. Reduced hole to 12-1/4". Drilled plug and resumed drilling.

3. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Juanita Goodlett TITLE Engineering Secretary DATE 10-6-82

ORIGINAL SIGNED BY

APPROVED BY JERRY SEXTON TITLE DISTRICT 1 SUPR. DATE OCT 12 1982

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

OCT 8 1982

C.C.D.  
NORRIS OFFICE