

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State ☐ Fee ☒

5. State Oil & Gas Lease No.

NONE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO CLEAN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name NONE
2. Name of Operator HILLIARD OIL & GAS, INC.	8. Farm or Lease Name MOSS FNB
3. Address of Operator 3000 North Garfield, Suite 120 Midland, TX 79705	9. Well No. 1
4. Location of Well UNIT LETTER <u>D</u> <u>660'</u> FEET FROM THE <u>North</u> LINE AND <u>660'</u> FEET FROM THE <u>West</u> LINE, SECTION <u>26</u> TOWNSHIP <u>12 S</u> RANGE <u>37 E</u> NMPM.	10. Field and Pool, or Wildcat SW Gladiola, Devonian
15. Elevation (Show whether DF, RT, GR, etc.) 3890.1' GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Spudded well @ 5:30 PM 9-25-82.
2. Drilled 17½" hole to 407'.
3. Set 13-3/8" 54.5# K-55 ST&C csg @ 405' w/425 sx Cl "C" + 2% calcium chloride + ¼# flocele per sack. Circulated 100 sx cement. Plug down @ 12:15 PM 9-26-82.
4. Drilled 11" hole to 4461'.
5. Set 8-5/8" 24# K-55 & 28# S-80 csg @ 4447". Cemented w/2200 sx Halco lite + additives followed w/300 sx Cl "C" neat. Circ 212 sx cement. Plug down @ 11:30 AM 10-6-82.
6. Installed well head & BOP's. Tested BOP's w/3000#.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Pat Coley TITLE Drilling Engineer DATE 2-15-83

Pat Coley

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT 1 SUPERVISOR TITLE  DATE FEB 22 1983

CONDITIONS OF APPROVAL, IF ANY: