

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
Rustler	1660	T. Canyon		T. Ojo Alamo		T. Penn. "B"	
T. Anhy		T. Strawn		T. Kirtland-Fruitland		T. Penn. "C"	
T. Salt	Base 2533	T. Atoka		T. Pictured Cliffs		T. Penn. "D"	
T. Salt		T. Miss		T. Cliff House		T. Leadville	
T. Yates	2648	T. Devonian		T. Menefee		T. Madison	
T. 7 Rivers		T. Silurian		T. Point Lookout		T. Elbert	
T. Queen	3422	T. Montoya		T. Mancos		T. McCracken	
T. Grayburg		T. Simpson		T. Gallup		T. Ignacio Qtzte	
T. San Andres	4088	T. McKee		Base Greenhorn		T. Granite	
T. Glorieta		T. Ellenburger		T. Dakota		T.	
T. Paddock		T. Gr. Wash		T. Morrison		T.	
T. Blinberry		T. Granite		T. Todilto		T.	
T. Tubb	7013	T. Delaware Sand		T. Entrada		T.	
T. Drinkard		T. Bone Springs		T. Wingate		T.	
T. Abo	7760	T. XX Marker	9376	T. Chinle		T.	
T. Wolfcamp	Ls 9101			T. Permian		T.	
T. Penn.				T. Penn. "A"		T.	
T. Cisco (Bough C)	9982						

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet.
No. 2, from.....to.....	feet.
No. 3, from.....to.....	feet.
No. 4, from.....to.....	feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1520	1520	Surface, Redbeds, Anhydrite				
1520	2560	1040	Redbeds, Salt				
2560	3640	1080	Anhydrite, Salt				
3640	4282	642	Anhydrite				
4282	4656	374	Dolomite, Anhydrite				
4656	5790	1134	Dolomite				
5790	6320	530	Dolomite, Lime				
6320	6768	448	Dolomite				
6768	7763	995	Dolomite, Lime				
7763	8059	296	Dolomite, Lime, Shale				
8059	8707	648	Lime, Shale				
8707	9535	828	Shale, Dolomite				
9535	10160	625	Lime, Shale, Dolomite				

RECEIVED

JAN 17 1983

O.C.D.
HOBBS OFFICE