

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> For <input type="checkbox"/>
5. State Oil & Gas Lease No.
K-4670

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amoco Production Company	8. Farm or Lease Name State DY
3. Address of Operator P. O. Box 68, Hobbs, New Mexico 88240	9. Well No. 1
4. Location of Well UNIT LETTER <u>K</u> <u>1953</u> FEET FROM THE <u>West</u> LINE AND <u>1980</u> FEET FROM THE <u>South</u> LINE, SECTION <u>19</u> TOWNSHIP <u>13-S</u> RANGE <u>33-E</u> N.M.P.M.	10. Field and Pool, or Wildcat Baum-Upper Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4292.8 GL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On 11-22-82, Moranco #7 spudded a 17-1/2" hole and drilled to a total depth of 450'. Ran 13-3/8" 40#/ft. H-40 casing. Casing set at 450'. Cemented with 475 sx class C with 1% CACL. Circulated 270 sx cement. WOC 18 hrs. Pressure tested casing to 950 psi. for 30 min. Held OK. Reduced bit to 11" and resumed drilling. On 11-30-82, drilled to total depth of 4047'. Ran 8-5/8" 32#/ft. K-55 casing. Casing set at 4040'. Cemented with 2150 sx lite with additives and 400 sx class C. Circulated 756 sx. WOC 18 hrs. Pressure tested casing to 600 psi for 30 min. Held OK. Reduced bit to 7-7/8" and resumed drilling. Currently drilling.

0+4-NMOC,D,H 1-HOU 1-W. Stafford, HOU 1-CMH

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Charles M. Herring TITLE Assist. Admin. Analyst DATE 12-6-82  
ORIGINAL SIGNED BY JERRY SEXTON  
APPROVED BY DISTRICT 1 SUPR. TITLE  DATE DEC 9 1982  
CONDITIONS OF APPROVAL

RE

RECEIVED

DEC 8 1982

NOBLE OFFICE