

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

O CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease

State ☒Fee ☐

5. State Oil & Gas Lease No.

LH-1656

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)OIL
WELL ☐GAS
WELL ☐

OTHER- DRY (P & A)

Name of Operator

CLEMENTS ENERGY, INC.

Address of Operator

P. O. Box 20500, Oklahoma City, Oklahoma 73156

Location of Well

UNIT LETTER A 810 FEET FROM THE North LINE AND 660 FEET FROM
THE East LINE, SECTION 14 TOWNSHIP 14-South RANGE 34-East R.M.P.M.

7. Unit Agreement Name

8. Farm or Lease Name

MGF NM 14 STATE COM

9. Well No.

1

10. Field and Pool, or Wildcat
Undesignated
High Plains Penn

15. Elevation (Show whether DF, RT, GR, etc.)

4093' GR

12. County

LEA

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐PLUG AND ABANDON ☐REMEDIAL WORK ☐ALTERING CASING ☐TEMPORARILY ABANDON ☐COMMENCE DRILLING OPNS. ☐PLUG AND ABANDONMENT ☒REPAIR OR ALTER CASING ☐CHANGE PLANS ☐CASING TEST AND CEMENT JOBS ☐OTHER ☐OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-6-83: TD 10,800'. Logging.

7-7-83: TD 10,800'. Finished logging.

7-8-83: TD 10,800'. DST #1 from 10,330' - 10,665'.

7-9 to.

7-12-83: TD 10,800'. Fishing DST tools. Top of Fish left in hole is 10,515'. Fish consists of bottom recorder, 2 perf. jts, 8 D.C.'s and 2 packers.

7-12-83: TD 10,800'. P & A. Cemented with 285 sxs Class "H" w/.4% WR2, 8.9#/gal. Set 35 sx plug from TQF @ 10,515'-10,470'; set 35 sx plug from 10,280'-10,230'; set 35 sx plug from 9598'-9528'; set 35 sx plug from 8050'-7992'; set 35 sx plug from 7310'-7252'; set 50 sx plug from 4548'-4493'; set 50 sx plug from 1700'-1645'; set 10 sx plug in top of surface and welded on ID Cap. Rig Released at 5:00 P.M. 7/12/83.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

By Richard H. LammTITLE Division EngineerDATE July 19, 1983By David CalomachTITLE OIL & GAS INSPECTORDATE NOV 22 1983