

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or completed well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico			Northwestern New Mexico		
Rustler					
T. Anhy	1702	T. Canyon	T. Ojo Alamo	T. Penn. "B"	
T. Salt Base	2550	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"	
T. Salt		T. Atoka	T. Pictured Cliffs	T. Penn. "D"	
T. Yates	2665	T. Miss	T. Cliff House	T. Leadville	
T. 7 Rivers		T. Devonian	T. Menefee	T. Madison	
T. Queen	3440	T. Silurian	T. Point Lookout	T. Elbert	
T. Grayburg		T. Montoya	T. Mancos	T. McCracken	
T. San Andres	4060	T. Simpson	T. Gallup	T. Ignacio Qtzite	
T. Glorieta	5615	T. McKee	Base Greenhorn	T. Granite	
T. Paddock		T. Ellenburger	T. Dakota		
T. Blinberry		T. Gr. Wash	T. Morrison		
T. Tubb	7027	T. Granite	T. Todilto		
T. Drinkard		T. Delaware Sand	T. Entrada		
T. Abo	7762	T. Bone Springs	T. Wingate		
T. Wolfcamp Ls	9112	T. XX Marker	9330	T. Chinle	
T. Penn.		T. Virgilian	9741	T. Permian	
T. Cisco (Bough C)				T. Penn. "A"	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet	
No. 2, from.....to.....feet	
No. 3, from.....to.....feet	
No. 4, from.....to.....feet	

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	650	650	Surface, Redbeds				
650	1725	1075	Redbeds, Anhydrite				
1725	3780	2055	Anhydrite, Salt				
3780	3882	102	Anhydrite				
3882	3971	89	Dolomite				
3971	4173	202	Anhydrite				
4173	7707	3534	Dolomite				
7707	7860	153	Dolomite, Shale				
7860	8032	172	Shale				
8032	8182	150	Lime, Shale				
8182	9284	1102	Dolomite, Shale				
9284	9373	89	Lime, Shale				
9373	9415	42	Dolomite, Lime, Shale				
9415	10105	690	Lime, Shale				
10105	10155	50	Dolomite, Shale				