

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-28137

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

V-644

7. Lease Name or Unit Agreement Name

Paloma WW State

8. Well No.

1

9. Pool name or Wildcat

~~South Baum Wolfcamp~~

1. Type of Well:

OIL  
WELL ☒

GAS  
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South Fourth Street - Artesia, NM 88210

4. Well Location

Unit Letter F : 1980 Feet From The North Line and 1980 Feet From The West Line

Section

3

Township

14S

Range

33E

NMPM

Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

4236.1' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Acidize existing perms & add new perms ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-21-94 - Moved in and rigged up pulling unit. Unseat pump. TOOH with pump and rods. Released tubing anchor. Strip on BOP. TOOH with production tubing. TIH w/10K RBP and packer.

6-22-94 - Straddled perforations 9845-9886'. Acidized with 1300 gallons 15% NEFE acid with scale inhibitor. Straddled perforations 9737-9806'. Acidized with 2700 gallons 15% NEFE acid with scale inhibitor. Released tools. Pulled up and set RBP at 9265'. Tested to 1000#. Loaded annulus and tested to 500 psi. TOOH with packer. WIH w/4" casing guns and perforated 9038-9213' w/28 .42" holes as follows: 9038-9041' (8 holes); 9156-9159' (8 holes) and 9206-9213' (12 holes). TIH w/packer and RBP. Set RBP at 9240'.

6-23-94 - Pumped 50 barrels 2% KCL down tubing. Did not circulate. Set packer and acidized perforations 9206-9213' w/2000 gallons 15% NEFE acid with scale inhibitor. Moved tools. Straddled perforations 9156-9159'. Spot acid to packer. Acidized perforations 9156-9159' with 2000 gallons 15% NEFE acid. Moved tools. Straddled perforations 9038-41'. Acidized with 2000 gallons 15% NEFE acid with scale inhibitor. Moved tools. Straddled perforations 9038-9213'. Swabbed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Rusty Klein*

TITLE

Production Clerk

DATE 6-24-94

TYPE OR PRINT NAME

Rusty Klein

505-748-1471  
TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT I SUPERVISOR

JUN 28 1994

TITLE

DATE

SECRETARY

1917

U.S. DEPT. OF  
OFFICE