STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

we. er Comits acctives	
DISTRIBUTION	
SANTA FE	
FILE	
U.\$ G.\$.	<u> </u>
LAHO OFFICE	
0.5.5.4.7.0.5	1

OIL CONSERVATION DIVISION

salt, 1/4#/sack flocele. Bumped plug to 950 psi, WOC. Drilled out 4:15 P. for 30 minutes, okay. R	Tailed in w/200 sacks Class "C' released pressure and float held PM 2-14-83. WOC 18 hours. Nipple Reduced hole to 7-7/8". Drilled produced hole to 7-7/8". Production Successful Services and complete to the best of my knowledge and the complete to the best of my knowledge.	sacks Halliburton Lite, 5#/sack " 2% CaCl2. PD 10:15 PM 2-13-83. okay. Cement circulated 50 sacks. ed up and tested to 1000 psi plug and resumed drilling.
shoe at 4200'. Insert f. salt, 1/4#/sack flocele. Bumped plug to 950 psi, WOC. Drilled out 4:15 P. for 30 minutes, okay. R	loat at 4160'. Cemented w/2000 so Tailed in w/200 sacks Class "C' released pressure and float held PM 2-14-83. WOC 18 hours. Nipple Reduced hole to 7-7/8". Drilled provided the complete to the best of my knowledge and	sacks Halliburton Lite, 5#/sack " 2% CaCl2. PD 10:15 PM 2-13-83. okay. Cement circulated 50 sacks. ed up and tested to 1000 psi plug and resumed drilling.
shoe at 4200'. Insert f. salt, 1/4#/sack flocele. Bumped plug to 950 psi, WOC. Drilled out 4:15 P. for 30 minutes, okay. R	loat at 4160'. Cemented w/2000 s Tailed in w/200 sacks Class "C' released pressure and float held PM 2-14-83. WOC 18 hours. Nipple Reduced hole to 7-7/8". Drilled	sacks Halliburton Lite, 5#/sack " 2% CaCl2. PD 10:15 PM 2-13-83. okay. Cement circulated 50 sacks. ed up and tested to 1000 psi plug and resumed drilling.
shoe at 4200'. Insert f. salt, 1/4#/sack flocele. Bumped plug to 950 psi, WOC. Drilled out 4:15 P.	Tailed in w/200 sacks Class "C" released pressure and float held PM 2-14-83. WOC 18 hours. Nipple	sacks Halliburton Lite, 5#/sack " 2% CaCl2. PD 10:15 PM 2-13-83. okay. Cement circulated 50 sacks. ed up and tested to 1000 psi
shoe at 4200'. Insert f. salt, 1/4#/sack flocele. Bumped plug to 950 psi, WOC. Drilled out 4:15 P.	Tailed in w/200 sacks Class "C" released pressure and float held PM 2-14-83. WOC 18 hours. Nipple	sacks Halliburton Lite, 5#/sack " 2% CaCl2. PD 10:15 PM 2-13-83. okay. Cement circulated 50 sacks. ed up and tested to 1000 psi
shoe at 4200'. Insert f. salt, 1/4#/sack flocele. Bumped plug to 950 psi, WOC. Drilled out 4:15 P.	Tailed in w/200 sacks Class "C" released pressure and float held PM 2-14-83. WOC 18 hours. Nipple	sacks Halliburton Lite, 5#/sack " 2% CaCl2. PD 10:15 PM 2-13-83. okay. Cement circulated 50 sacks. ed up and tested to 1000 psi
shoe at 4200'. Insert f. salt, 1/4#/sack flocele. Bumped plug to 950 psi, WOC. Drilled out 4:15 P.	Tailed in w/200 sacks Class "C" released pressure and float held PM 2-14-83. WOC 18 hours. Nipple	sacks Halliburton Lite, 5#/sack " 2% CaCl2. PD 10:15 PM 2-13-83. okay. Cement circulated 50 sacks. ed up and tested to 1000 psi
shoe at 4200'. Insert f. salt, 1/4#/sack flocele. Bumped plug to 950 psi, WOC. Drilled out 4:15 P.	Tailed in w/200 sacks Class "C" released pressure and float held PM 2-14-83. WOC 18 hours. Nipple	sacks Halliburton Lite, 5#/sack " 2% CaCl2. PD 10:15 PM 2-13-83. okay. Cement circulated 50 sacks. ed up and tested to 1000 psi
shoe at 4200'. Insert f. salt, 1/4#/sack flocele. Bumped plug to 950 psi, WOC. Drilled out 4:15 P.	Tailed in w/200 sacks Class "C" released pressure and float held PM 2-14-83. WOC 18 hours. Nipple	sacks Halliburton Lite, 5#/sack " 2% CaCl2. PD 10:15 PM 2-13-83. okay. Cement circulated 50 sacks. ed up and tested to 1000 psi
shoe at 4200'. Insert f. salt, 1/4#/sack flocele. Bumped plug to 950 psi, WOC. Drilled out 4:15 P.	Tailed in w/200 sacks Class "C" released pressure and float held PM 2-14-83. WOC 18 hours. Nipple	sacks Halliburton Lite, 5#/sack " 2% CaCl2. PD 10:15 PM 2-13-83. okay. Cement circulated 50 sacks. ed up and tested to 1000 psi
shoe at 4200'. Insert f. salt, 1/4#/sack flocele. Bumped plug to 950 psi, WOC. Drilled out 4:15 P.	Tailed in w/200 sacks Class "C" released pressure and float held PM 2-14-83. WOC 18 hours. Nipple	sacks Halliburton Lite, 5#/sack " 2% CaCl2. PD 10:15 PM 2-13-83. okay. Cement circulated 50 sacks. ed up and tested to 1000 psi
shoe at 4200'. Insert f. salt, 1/4#/sack flocele. Bumped plug to 950 psi, WOC. Drilled out 4:15 P.	Tailed in w/200 sacks Class "C" released pressure and float held PM 2-14-83. WOC 18 hours. Nipple	sacks Halliburton Lite, 5#/sack " 2% CaCl2. PD 10:15 PM 2-13-83. okay. Cement circulated 50 sacks. ed up and tested to 1000 psi
shoe at 4200'. Insert f	loat at 4160'. Cemented w/2000 s Tailed in w/200 sacks Class "C'	sacks Halliburton Lite, 5#/sack " 2% CaCl2. PD 10:15 PM 2-13-83.
Ran 102 joints of 8-5/8" shoe at 4200'. Insert f	loat at 4160'. Cemented w/2000 s	sacks Halliburton Lite, 5#/sack
	32 # J-55 ST&C casing set 4200 .	L-Toyge Pattorn notched guilde
work) SEE RULE 1103.		
OTHER	Clarely state all nestinent details, and nine pertin	ent dates, including estimated date of starting any proposed
	OTHER	ermediate Casing X
MPORARILY ABANDON	COMMENCE DRILLIN CHANGE PLANS CASING TEST AND C	
RFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
NOTICE OF INTENT	TION TO:	SUBSEQUENT REPORT OF:
Check Appro	priate Box To Indicate Nature of Notice	e, Report or Other Data
	15. Elevation (Show whether DF, RT, GR, etc.) 4234.5 GR	Lea
	3 TOWNSHIP 14S RANGE 33	MADE.
		(//////////////////////////////////////
ocation of Well F 1980	O FEET FROM THE NORTH LINE AND 660	10. Field and Pool, or Wildeat Lazy J Penn
207 South 4th St., Ar	rtesia, NM 88210	X D
Yates Petroleum Corpo	oration	Dove VK State 9. Well No.
well Well oth	ER-	8. Farm or Lease Name
OIL GAS		7. Unit Agreement Name
SUNDRY NOT	FICES AND REPORTS ON WELLS. TO DRICE ON TO DECEND ON PLUG BACK TO A DIFFERENT N PERMIT - " FROM C-1011 FOR SUCH PROPOSALS."	ESERVOIR.
		LG 2670
OPERATOR		State X Fee 5. State Oil 6. Gas Lease No.
U.S G.S. LAND OFFICE OPERATOR		
FILE U.S G.S. LAND OFFICE	5,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Sa. Indicate Type of Lease
U.S. G.S. LAND OFFICE	P. O. BOX 2088 SANTA FE, NEW MEXICO 8750	