

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B-9385	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
TEXACO Inc.		New Mexico "AN" State
3. Address of Operator		9. Well No.
P. O. Box 728, Hobbs, New Mexico 88240		11
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER D, 660 FEET FROM THE North LINE AND 660 FEET FROM		Saunders Permo Upper Penn
THE West LINE, SECTION 22 TOWNSHIP 14-S RANGE 33-E NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
4205' (GR)		Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TOTAL DEPTH 10,100'

13 3/8" OD 48# H-40 CSG SET @ 500'
8 5/8" OD 24# & 32# K-55 CSG SET @ 4190'

1. Ran 10,087' 5 1/2" OD . 20# L-80 Buttress & 17# J-55 Csg & set @ 10,100'
2. Cemented 1st Stage W/700 sx, HLW Cement containing 10# Gilsonite, 1# Flocele, & .6% Halad 9 per sack. Follow W/200 Sx. 50-50 Pozmix & Class 'H' Cement containing 6# Gilsonite, 1# Flocele, & .8% Halad 9 per sack.
3. With DV Tool open @ 7052', cement 2nd stage W/1320 sx. LW Cement, 10# Gilsonite, 1# Flocele & .2% HR-5 per sack. Cement circulate. Job complete 2:45 PM, 8-1-83

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Asst. Dist. Mgr. DATE 8-2-83

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON TITLE DISTRICT 1 SUPERVISOR DATE AUG 5 1983
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
AUG 4 1983
FEDERAL OFFICE