

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR

Coastal Oil & Gas Corporation

3. ADDRESS OF OPERATOR

P. O. Box 235 Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL & 1980' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☒
☐
☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED
JAN 16 9 25 AM '84
BUR. OF LAND MGMT.
ROSEBUD DISTRICT

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 11-23 RU well service unit. Run GR/CBL 9808-7808'. TOC-8012'.
PU 4 3/4" bit, bit sub, RIH on 168 jts 2 3/8" tbg.
- 11-24 SD for holiday
- 11-25 FIH w/tbg & bit. Drill cmt. 9808-9830'. Circ clean. POOH.
LD bit & sub. GIH w/pkr & tbg.
- 11-26 Spot 2 bbl acid. Set pkr @ 9706'. Perf 9777-83', 92-96', &
9812-17 w/2 SPF using tbg gun. Treat w/3000 gal 15% NE-FE acid.
Treat 1.8 BPM @ 5600 psi. Flow & swab 95 BF in 5 hrs.
- 11-27 Swabbing
- 11-28 Swab 3 1/2 hr. Rel pkr & POOH. LD pkr. PU RBP & RTTS & RIH. Set
RBP @ 9755'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED P. J. Campbell TITLE Sr. Petroleum Engr DATE January 12, 1984

ACCEPTED FOR RECORD (This space for Federal or State office use)
PETER W. CHESTER
APPROVED BY _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:
FEB 17 1984

RECEIVED
MAR 2 1984
OCD.
HOBBS OFFICE

11-29 Spot acid. Set RTTS @ 9675'. Perf 9720-40' w/2 SPF using
tbg gun. Treat w/4000 gal 15% NE-FE acid. Treat 5.2 BPM @
1600 psi. Swab 54 BLW in 5 hr.

11-30 Swabbing

12-01 Swabbing

12-02 Swabbing. RIH w/BHP bomb.

12-03 SI

12-04 SI

12-05 Pulled BHP bomb. Rel. RTTS, retrieve RBP. POOH. RIH
w/prod. equipment.

12-06 Running production equipment.

12-07 Running production equipment.

12-08 Installed pumping unit.

12-09 Set pumping unit. Laying flowline

12-10 Laying flowline

12-11 Laying flowline

12-12 Started pumping.

RECEIVED
MAR 2 1984
O.C.D.
HOBBS OFFICE