

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1165.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Rustler		Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	1650	T. Canyon		T. Ojo Alamo	T. Penn. "B"
T. Salt		T. Strawn		T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	2541	T. Atoka		T. Pictured Cliffs	T. Penn. "D"
T. Yates	2650	T. Miss		T. Cliff House	T. Leadville
T. 7 Rivers		T. Devonian		T. Menefee	T. Madison
T. Queen	3422	T. Silurian		T. Point Lookout	T. Elbert
T. Grayburg		T. Montoya		T. Mancos	T. McCracken
T. San Andres	4095	T. Simpson		T. Gallup	T. Ignacio Qtzite
T. Glorieta	5571	T. McKee		Base Greenhorn	T. Granite
T. Paddock		T. Ellenburger		T. Dakota	
T. Blinberry		T. Gr. Wash		T. Morrison	
T. Tubb	6998	T. Granite		T. Todilto	
T. Drinkard		T. Delaware Sand		T. Entrada	
T. Abe	7734	T. Bone Springs		T. Wingate	
T. Wolfcamp	LS 9083	T. XX Marker	9308	T. Chinle	
T. Penn.		T. Virgilian	9770	T. Permian	
T. Cisco (Bough C)		T. Dolomite	10220	T. Penn. "A"	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 4, from.....to.....
 No. 2, from.....to..... No. 5, from.....to.....
 No. 3, from.....to..... No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....
 No. 4, from.....to.....feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	50	50	Surface, Rock				
50	1653	1603	Redbeds				
1653	3824	2171	Anhydrite, Salt				
3824	4300	476	Anhydrite				
4300	4380	80	Dolomite, Anhydrite				
4380	5000	620	Dolomite				
5000	5520	520	Dolomite, Shale, Limestone				
5520	5800	280	Dolomite, Sand, Chert, Anhydrite				
5800	6100	300	Anhydrite, Dolomite				
6100	6740	640	Anhydrite, Sand, Dolomite				
6740	7320	580	Dolomite, Anhydrite, Sand				
7320	9100	1780	Dolomite, Anhydrite, Shale				
9100	9700	600	Dolomite, Shale, Chert				
9700	9840	140	Dolomite, Limestone, Shale				
9840	10240	400	Lime, Shale				