Submit 3 Copies to Appropriate District Office

DISTRICT II

1. Type of Well:

WELL X

2. Name of Operator

3. Address of Operator

Section

PERFORM REMEDIAL WORK

TEMPORARILY ABANDON

PULL OR ALTER CASING

4. Well Location

11.

State of New Mexico Energy, Minerals and Natural Resources Department

DISTRICT P.O. Box 1980, Hobbs, NM 88240

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410

MWJ PRODUCING COMPANY

10

Unit Letter _L

GAS F

Form C-103 Revised 1-1-89 OIL CONSERVATION DIVISION WELL API NO. P.O. Box 2088 *30-025-*28*37*9 Santa Fe, New Mexico 87504-2088 5. Indicate Type of Lease STATE X FEE 6. State Oil & Gas Lease No. LG-2612 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) SAUNDERS 10 STATE OTHER 8. Well No. 9. Pool name or Wildcat 400 W. Illinois - Suite 1100 Midland, Texas 79701 Saunders Permo Upper Penn : 1980 Feet From The South Line and 660 __ Feet From The <u>West</u> 14S 33E Range Township **NMPM** County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4212.8' GL Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PLUG AND ABANDON REMEDIAL WORK **ALTERING CASING CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: Perf "B" zone 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed

work) SEE RULE 1103.

MI & RU PU. Removed W/H assy & pulled 1" vent string. Removed dual lange & POOH w/2-3/8" tbg & BHA. RU Wedge W/L, ran & set CIBP @ 9910'. 2/23-26: SD due to bad weather and Christmas Holidays.

2/27/89: Ran 318 jts 2-3/8" buttress thread tbg, EOT @ 9900'. Circ hole & tstd lug to 2000 psi. Spt'd 1000 glas 15% HCL ac. RU Wedge W/L & Perf'd "B" zone from 820-24', 9834-42', 9866-70' & 9880-9888' 2 SPF w/4" OD csg gun. Ran Baker R-3 pkr, SN, CO & 314 jts 2-3/8" tbg. Set pkr @ 9878.89' w/14000# tension, SN @ 9780.79'. Swbd. Acd w/2000 gals 15% HCL ac & 50 7/8" 1/2 sp grav ball sealers @ 2/28/89:

BPM @ 2000 psi. Swbd.

Ran tbg, top of pkr @ 9794.58', EOT @ 9896.88'. Ran 1" seal assy. 2/29/89: Swbd. Ran 1" vent string. Ran pump. RD & MO.

(This apace for State Use)		JAN 1 6 1990
TYPE OR PRINT NAME		TELEPHONE NO.
I hereby certify that the information above is true and complete to the best of my knowledge and belief SIGNATURE TITLE	Pat Drexler-Agent	DATE 1/5/90

ORIGINAL SIGNED BY DISTRICT I SUPERVISOR

CONDITIONS OF APPROVAL; IF ANY:

APPROVED BY.