

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
K-3657	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		7. Unit Agreement Name
2. Name of Operator Cabot Petroleum Corporation		8. Farm or Lease Name New Mexico 'T' State
3. Address of Operator P. O. Box 5001, Pampa, Texas 79065		9. Well No. 5
4. Location of Well UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM West LINE, SECTION 4 TOWNSHIP 14S RANGE 33E N.M.P.M.		10. Field and Pool, or WHdcat Baum Upper Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4235' GR		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Drilled to 10,200' T.D. K.B. to Braidenhead 17'. Ran 1551' of 5½" 20# and 4603' of 5½" 17# N-80, and 342' of 5½" 17# and 3685' of 5½" 20# P110 LT&C casing to 10,183', set at 10,200' and cemented with 750 sacks Class H with 5# salt, .4% CFR2, .3% Halad 228. Plug down at 2:30 pm MST 12/6/83.
- After WOC 72 hours, tested with 1500 psi for 30 minutes. Tested o.k.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Evelyn Farmer TITLE Agent DATE 12/12/83

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON TITLE DISTRICT 1 SUPERVISOR DATE DEC 14 1983  
CONDITIONS OF APPROVAL, IF ANY: