

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
T. Anhy	1457	T. Canyon		T. Ojo Alamo		T. Penn. "B"	
T. Salt		T. Strawn		T. Kirtland-Fruitland		T. Penn. "C"	
B. Salt	2427	T. Atoka		T. Pictured Cliffs		T. Penn. "D"	
T. Yates	2501	T. Miss		T. Cliff House		T. Leadville	
T. 7 Rivers		T. Devonian		T. Menefee		T. Madison	
T. Queen	3266	T. Silurian		T. Point Lookout		T. Elbert	
T. Grayburg		T. Montoya		T. Mancos		T. McCracken	
T. San Andres	3873	T. Simpson		T. Gallup		T. Ignacio Qtzite	
T. Glorieta	5489	T. McKee		Base Greenhorn		T. Granite	
T. Paddock		T. Ellenburger		T. Dakota		T.	
T. Blinberry		T. Gr. Wash		T. Morrison		T.	
T. Tubb	6875	T. Granite		T. Todillo		T.	
T. Drinkard		T. Delaware Sand		T. Entrada		T.	
T. Abo	7614	T. Bone Springs		T. Wingate		T.	
T. Wolfcamp Ls	9008	XX Marker	9143	T. Chinle		T.	
T. Penn.		Virgilian	9603	T. Permian		T.	
T. Chap (Bough C)	9694	Dolomite	10046	T. Penn. "A"		T.	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
No. 2, from.....to.....feet.....
No. 3, from.....to.....feet.....
No. 4, from.....to.....feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	450	450	Surface	9000	9140	140	Dolomite, Limestone, Shale
450	1490	1040	Redbeds	9140	9600	460	Chert, Dolo, Shale, Lime
1490	2450	960	Redbeds, Salt, Anhydrite	9600	9680	80	Dolomite, Lime, Shale
2450	4200	1750	Anhydrite, Lime	9680	10080	400	Lime, Shale
4200	4740	540	Dolomite				
4740	5020	280	Dolomite, Chert, Shale, Anhy.				
5020	5240	220	Dolomite, Anhydrite				
5240	5360	120	Dolomite, Lime, Anhydrite				
5360	5460	100	Dolomite, Lime, Sand				
5460	5820	360	Anhydrite, Dolo, Lime, Sand				
5820	5880	60	Anhy, Dolomite, Shale				
5880	6140	260	Dolomite, Anhydrite, Sand				
6140	6400	260	Dolomite, Anhydrite, Shale				
6400	7640	1240	Dolomite, Anhydrite, Sand, Shale				
7640	9000	1360	Shale, Anhydrite, Dolomite				