

10-113

Artesia Petroleum Corporation

207 South 4th St., Artesia, NM 88210

WELL NO. 10-113

Tub. Perm.

1580

South

27-6

148

148

148

148

7322' OR

Production Supervisor

Production Supervisor

Production Supervisor, Artesia

10-113 (10-113)'. Ran 254 ft. of 5-1/2" 17# casing set at 10940'. Cement collar set at 10944'. Cemented w/700 sacks Class "H", .32 RD, 1% friction reducer and 1% additive. Cased in w/300 sacks Class "H", .32 RD, 1% friction reducer and 1% additive. Compressive strength of cement = 920 psi @ 14 hours. At 4:30 PM 11-11-83, dumped clay to 1750 psi for 30 minutes, released pressure and float held dry. 10-113. and performed 2602-14' w/10 .50" holes as follows: 9802, 93, 04, 09, 10, 11, 12, 13, and 15'. Ran tubing and packer. Spotted acid across perfor. Acidiz w/ 900 gallons of 15% HCl. Followed w/1 bbl each corrosion and scale inhibitor. 5000 gallons of 15% HCl. and 1 bbl each. Swabbed well. 9000' w/packer and P.P. set on final casing and

This report is based on the information above is true and complete. No test of new information is required.

Production Supervisor

10-113-113

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

EXTON

DEC 27 1983

Artesia Petroleum Corporation