

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
T. Rustler	1535	T. Canyon		T. Ojo Alamo		T. Penn. "B"	
T. Anhy		T. Strawn		T. Kirtland-Fruitland		T. Penn. "C"	
T. Salt	2471	T. Atoka		T. Pictured Cliffs		T. Penn. "D"	
T. Salt	2541	T. Miss		T. Cliff House		T. Leadville	
T. Yates		T. Devonian		T. Menefee		T. Madison	
T. 7 Rivers		T. Silurian		T. Point Lookout		T. Elbert	
T. Queen	3310	T. Montoya		T. Mancos		T. McCracken	
T. Grayburg		T. Simpson		T. Gallup		T. Ignacio Qtzite	
T. San Andres	3950	T. McKee		T. Base Greenhorn		T. Granite	
T. Glorieta	5550	T. Ellenburger		T. Dakota			
T. Paddock		T. Gr. Wash		T. Morrison			
T. Blinberry		T. Granite		T. Todilto			
T. Tubb	6911	T. Delaware Sand		T. Entrada			
T. Drinkard		T. Bone Springs		T. Wingate			
T. Abo	7642	T. XX Marker	9195	T. Chinle			
T. Wolfcamp	LS 8914	T. Dolomite	10160	T. Permian			
T. Penn.				T. Penn. "A"			
T. Cisco (Bough C)							

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
No. 2, from.....to.....feet.....
No. 3, from.....to.....feet.....
No. 4, from.....to.....feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	454	454	Surface, Redbeds	7000	7360	360	Dolomite, Anhy, Shale
454	2552	2098	Redbeds, Anhydrite	7360	7660	300	Dolomite, Anhydrite
2552	2940	388	Dolomite, Redbeds, Salt	7660	7760	100	Shale, Dolomite
2940	4200	1260	Anhydrite	7760	8920	1160	Anhydrite, Dolo, Shale
4200	4620	420	Dolomite	8920	9080	160	Dolomite, Lime, Shale
4620	4740	120	Dolo, Sand, Chert, Shale	9080	9520	440	Chert, Dolo, Lime, Shale
4740	4900	160	Dolomite, Anhydrite	9520	10200	680	Lime, Shale
4900	5100	200	Dolo, Anhydrite, Sand				
5100	5220	120	Dolomite, Chert				
5220	5420	200	Dolo, Chert, Lime, Anhy.				
5420	5580	160	Dolo, Lime, Sand				
5580	5900	320	Anhy, Dolo, Sand, Lime				
5900	6120	220	Anhy, Dolo, Sand				
6120	6240	120	Dolomite, Sand				
6240	6960	720	Dolomite				
6960	7000	40	Dolo, Sand, Shale				