

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.  
LG 8294

**SUNDRY NOTICES AND REPORTS ON WELLS**  
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - FORM C-1011 FOR SUCH PROPOSALS.

OIL WELL  GAS WELL  OTHER

Name of Operator  
Yates Petroleum Corporation

Address of Operator  
207 South 4th St., Artesia, NM 88210

Location of Well  
UNIT LETTER M 660 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE SECTION 22 TOWNSHIP 14S RANGE 32E

11. Elevation (Show whether DF, RT, GR, etc.)  
4315.1' GR

7. Unit Agreement Name

8. Form or Lease Name  
Heyco YL State

9. Well No.  
1

10. Field and Pool, or Wildcat  
Undes. Tulk Penn

12. County

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
FULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER Intermediate Casing <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 95 jts of 8-5/8" 32# J-55 casing set 4180'. 1-Texas Pattern notched guide shoe set 4180'. Insert float set 4136'. Cemented w/2000 sacks Pacesetter "C" Lite, 5#/sack salt, 1/4#/sack celloseal. Tailed in w/200 sacks Class "C", 1/4#/sack celloseal. Compressive strength of cement - 1050 psi in 12 hrs. PD 9:30 PM 1-22-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out 3:45 PM 1-23-84. WOC 18 hours and 15 minutes. Nippled up and tested to 1000 psi for 30 minutes, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signature: [Signature] TITLE: Production Supervisor DATE: 2-8-84

Signature: [Signature] TITLE: Oil & Gas Inspector DATE: FEB 10 1984

CONDITIONS OF APPROVAL, IF ANY: