

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
Rustler	1682	T. Canyon		T. Ojo Alamo		T. Penn. "B"	
T. Anhy		T. Strawn		T. Kirtland-Fruitland		T. Penn. "C"	
T. Salt	2540	T. Atoka		T. Pictured Cliffs		T. Penn. "D"	
B. Salt	2654	T. Miss		T. Cliff House		T. Leadville	
T. Yates		T. Devonian		T. Menefee		T. Madison	
T. 7 Rivers		T. Silurian		T. Point Lookout		T. Elbert	
T. Queen	3430	T. Montoya		T. Mancos		T. McCracken	
T. Grayburg	4102	T. Simpson		T. Gallup		T. Ignacio Qtzite	
T. San Andres	5583	T. McKee		Base Greenhorn		T. Granite	
T. Glorieta		T. Ellenburger		T. Dakota			
T. Paddock		T. Gr. Wash		T. Morrison			
T. Blinberry		T. Granite		T. Todilto			
T. Tubb	7000	T. Delaware Sand		T. Entrada			
T. Drinkard		T. Bone Springs		T. Wingate			
T. Abo	7736	XX Marker	9304	T. Chinle			
T. Wolfcamp Ls	9076	T. Virgilian	9762	T. Permian			
T. Penn.				T. Penn. "A"			
T. Cisco (Bough C)							

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet.
No. 2, from.....to.....	feet.
No. 3, from.....to.....	feet.
No. 4, from.....to.....	feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	560	560	Redbeds, Surface	6800	7180	380	Dolomite, Anhydrite, Sand
560	3341	2781	Redbeds, Anhydrite	7180	7600	420	Dolomite
3341	4200	859	Anhydrite, Salt Stringers	7600	8980	1380	Anhydrite, Dolomite, Shale
4200	5020	820	Dolomite	8980	9720	740	Dolomite, Shale, LS, Chert
5020	5480	460	Limestone, Shale	9720	10270	550	Shale, Limestone
5480	5600	120	Shale, Sandstone, Dolo.				
5600	5680	80	Anhy, Dolo, Lime, Sand				
5680	5880	200	Anhy, Dolo, Tr. Chert				
5880	6000	120	Anhydrite, Dolomite				
6000	6120	120	Anhydrite, Dolo, Sandstone				
6120	6200	80	Dolomite, Shale, Anhydrite				
6200	6300	100	Dolomite, Sand, Anhydrite				
6300	6460	160	Dolomite, Anhy, Shale, Sd				
6460	6800	340	Dolomite, Anhydrite, Chert				

RECEIVED
FEB 27 1984
O.C.D.
HOBBS OFFICE