

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-77

DATE RECEIVED	
DISTRIBUTION	
SANTEE	
FILE	
U.S. NO.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
LC 815

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS POINT FOR PROPOSALS TO DRILL OR TO RE-DRILL OR PLUG BACK TO A DIFFERENT RESERVOIR.
SEE APPLICATION FOR PERMIT - C-101 FOR SUCH PROPOSALS.)

DRILL ☒ GAS ☐
WELL ☐ OTHER ☐
Name of Operator:

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER E 1980 FEET FROM THE North LINE AND 660 FEET FROM
THE West LINE, SECTION 21 TOWNSHIP 14S RANGE 33E NMPL.

7. Unit Agreement Name

8. Farm or Lease Name

Woodpecker SY State

9. Well No.

8

10. Field and Pool, or Wildcat

Saunders Permo Upper Penn

15. Elevation (Show whether DF, RT, GR, etc.)

4223.4' GR

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data.

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

EXPLORE FEMERAL WORK ☐
TEMPORARILY ABANDON ☐
WELL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPERATIONS ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
Production Casing, Perforate, Treat ☒

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 10270'. Ran 242 jts of 5-1/2" 17# N-80 and J-55 LT&C casing as follows: 52 jts 5-1/2" 17# N-80; 155 jts 5-1/2" 17# J-55; 35 jts 5-1/2" 17# N-80 (total 10274') casing set 10270'. 1-regular guide shoe set 10270'. Float collar set 10230'. Cemented w/1030 sacks Class "H", 3% KCL, .6% CFR-2, .5% Halad-9. Compressive strength of cement - 950 psi in 12 hrs. PD 12:00 AM 1-9-84. Bumped plug to 1000 psi for 30 minutes, released pressure, float and casing held okay. WOC 18 hours. WIH and perforated 9913-39' w/18 .45" holes as follows: 9913, 14, 15, 18, 19, 20, 21, 22, 24, 26, 27, 28, 29, 30, 31, 35, 37 and 39'. Acidized perms w/4000 gallons 15% NE acid, 1% KCL and 17 ball sealers.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Juanita Goodlett

TITLE Production Supervisor

DATE 1-18-84

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON
CONDITIONS OF APPROVAL DISTRICT SUPERVISOR

TITLE

DATE JAN 24 1984

RECEIVED

JAN 28 1947

OF
HOES