

N. M. OIL CONS. COMMISSION
P. O. BOX 1900
HOBBS, NEW MEXICO 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Harvey E. Yates Company

3. Address and Telephone No.

P.O. Box 1933, Roswell, N.M. 88202

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit N; 660' FSL & 1980' FWL
Sec. 26, T13S, R35E

5. Lease Designation and Serial No.

NM-16648

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Duncan Unit #3

9. API Well No.

30-025-28535

10. Field and Pool, or Exploratory Area

Austin Mississippian, NW
11. County or Parish, State

Lea Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1) Set CIBP @ 13,000' w/50' cmt (by tbg) or 35' cmt (by bailer)
- 2) Spot 100' cmt plug 9659-9759'
- 3) Cut & pull 5 1/2" csg @ 9300 +/-
- 4) Spot 150' cmt plug over csg stub (75' in & 75' out); Tag plug
- 5) Spot 100' plug from 4470-4570'; tag plug
- 6) Spot 100' plug from 310-410'
- 7) Spot 50' surface plug @ surface & install dry hole marker

(NOTE: Above approved by Shannon Shaw 3/9/93)

14. I hereby certify that the foregoing is true and correct

Signed Tim Gum Tim Gum

Title Engineer

Date 3/8/93

(This space for Federal or State office use)

Approved by (ORIG. SGD.) DAVID R. GLASS
Conditions of approval, if any:

Title PETROLEUM ENGINEER

Date 3-9-93

SEE ATTACHED