

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
LG-1469	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)		
OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. Unit Agreement Name
Name of Operator Harvey E. Yates Company		8. Farm or Lease Name
Address of Operator P. O. Box 1933, Roswell, New Mexico 88201		9. Well No.
Location of Well UNIT LETTER <u>L</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>18</u> TOWNSHIP <u>14S</u> RANGE <u>33E</u> N.M.P.M.		10. Field and Pool, or Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4267' GR		12. County
		Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ WELL OR ALTER CASING ☐ OTHER ☐	PLUG AND ABANDON ☐ CHANGE PLANS ☐ OTHER ☐	REMEDIAL WORK ☒ COMMENCE DRILLING OPERATIONS ☐ CASING TEST AND CEMENT JOB ☒ OTHER ☐	ALTERING CASING ☐ PLUG AND ABANDONMENT ☐ OTHER ☐
--	---	---	--

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

4/8/84 Ran 5 1/2" csg as follows:

47	jts	17#	N-80	LT&C	1856.27'
45	jts	17#	J-55	LT&C	1982.9'
91	jts	15.5	J-55	LT&C	3671.05'
22	jts	17#	J-55	LT&C	959.77'
44	jts	17#	N-80	LT&C	1761.27'
249					10231.26

Set @ 10,200', cmt w/170 sx of CL "H" w/7.8# salt/sx, .7% TF-4/sx.

4/10/84 PBTB @ 10,122'. TOC @ 9668'.

4/13/84 Spot 500 gal 15% spearhead acid.

4/18/84 Set CIBP @ 10,050' Perf @ 10,004' to 10,008' w/2 jsf.

4/19/84 Spot 500 gal 15% Spearhead

4/24/84 Dump 35' cmt on top of CIBP @ 10,050'. Set cmt ret @ 10,000'.

4/25/84 Perf 2 holes @ 9990' 2 spf 9958' to 9962' & 9968' to 9980'.

4/26/84 Spot 500 gal 15% spearhead acid.

4/28/84 Acidize w/1500 gal spearhead.

5/01/84 Acidize w/5000 gal 20% spearhead & flush w/2% kcl.

5/03/84 Dump 35' cmt on top of ret @ 10,000'. Set CIBP @ 9940'.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton

TITLE Reservoir Engineer

DATE May 17, 1984

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY

TITLE

DATE MAY 21 1984

CONDITIONS OF APPROVAL

5/04/84 Perf from 9926'-14', 13', 12', 11', 03', 02', 9687', 9688' (1 spt)
 5/05/84 Acidize w/500 gal 20% Spearhead, spot acid @ 9926'.
 5/08/84 Acidize w/300 gal 20% Spearhead w/20 ball sealers.
 5/10/84 GIH w/2 3/8" tbg open ended. RD & Release CU.

HOBBS OFFICE