

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
Rustler	1676	T. Canyon		T. Ojo Alamo		T. Penn. "B"	
T. Anhy		T. Strawn		T. Kirtland-Fruitland		T. Penn. "C"	
T. Salt	2514	T. Atoka		T. Pictured Cliffs		T. Penn. "D"	
B. Salt	2624	T. Miss		T. Cliff House		T. Leadville	
T. Yates		T. Devonian		T. Menefee		T. Madison	
T. 7 Rivers		T. Silurian		T. Point Lookout		T. Elbert	
T. Queen	3381	T. Montoya		T. Mancos		T. McCracken	
T. Grayburg		T. Simpson		T. Gallup		T. Ignacio Qtzite	
T. San Andres	4039	T. McKee		Base Greenhorn		T. Granite	
T. Glorieta	5523	T. Ellenburger		T. Dakota		T.	
T. Paddock		T. Gr. Wash		T. Morrison		T.	
T. Blainebr		T. Granite		T. Todillo		T.	
T. Tubb	6938	T. Delaware Sand		T. Entrada		T.	
T. Drinkard		T. Bone Springs		T. Wingate		T.	
T. Abo	7696	T. XX Marker	9264	T. Chinle		T.	
T. Wolfcamp Ls	9045	T. Virgilian	9669	T. Permian		T.	
T. Penn.		T. Bough "C"	9823	T. Penn. "A"		T.	
T. Cisco (Bough C)							

OIL OR GAS SANDS OR ZONES

No. 1, from	to	No. 4, from	to
No. 2, from	to	No. 5, from	to
No. 3, from	to	No. 6, from	to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from	to	feet
No. 2, from	to	feet
No. 3, from	to	feet
No. 4, from	to	feet

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	448	448	Surface, Redbeds	6580	6960	380	Dolomite
448	2717	2269	Redbeds, Anhydrite	6960	7080	120	Dolomite, Sand
2717	4200	1483	Anhydrite, Salt	7080	7380	300	Dolomite
4200	5020	820	Dolomite	7380	7685	305	Dolomite, Anhydrite
5020	5080	60	Dolomite, Lime	7685	8940	1255	Dolo, Anhydrite, Shale
5080	5260	180	Limestone	8940	9080	140	Dolomite
5260	5520	260	Lime, Dolomite	9080	9210	130	Dolomite, Lime
5520	5740	220	Anhy, Lime, Dolo, Sand	9210	9620	410	Chert, Lime, Shale
5740	5900	160	Anhydrite, Dolomite	9620	10200	580	Lime, Shale
5900	6060	160	Dolomite				
6060	6300	240	Dolo, Anhy, Sand, Shale				
6300	6360	60	Dolomite, Anhydrite				
6360	6520	160	Dolomite				
6520	6580	60	Dolomite, Sand, Anhydrite				