

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
K-3846	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name	
2. Name of Operator Cabot Petroleum Corporation		8. Farm or Lease Name New Mexico 'U' State	
3. Address of Operator P. O. Box 5001, Pampa, TX 79065		9. Well No. 2	
4. Location of Well UNIT LETTER <u>B</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>4</u> TOWNSHIP <u>14S</u> RANGE <u>33E</u> N.M.P.M.		10. Field and Pool, or Wildcat Baum Upper Penn	
15. Elevation (Show whether DF, RT, GR, etc.) 4237' GR		12. County Lea	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPMS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Spudded well at 9:00 am MST 4/15/84. Moranco Drilling Company is the drilling contractor.
- Ran 13 3/8" H40, 48#, ST&C casing to 400', cemented with 450 sacks Class C 2% CaCl, 1/4# Flocele. Plug down at 4:10 pm MST 4/15/84. Cement circulated to surface.
- After WOC 18 hours, tested with 600 psi for 30 minutes. Tested o.k.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>E. L. Farmer</u>	TITLE <u>Agent</u>	DATE <u>4/19/84</u>
ORIGINAL SIGNED BY JERRY SEXTON DISTRICT I SUPERVISOR		
APPROVED BY _____	TITLE _____	DATE <u>APR 23 1984</u>
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED
APR 23 1984
HOBBS