

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-71

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
NM V-128 & V-120

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator MWJ PRODUCING COMPANY	8. Farm or Lease Name Baum 17 "B" State Com
3. Address of Operator 1804 First National Bank Bldg Midland, Texas 79701	9. Well No. 2
4. Location of Well UNIT LETTER <u>I</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>17</u> TOWNSHIP <u>14S</u> RANGE <u>33E</u> NMPM.	10. Field and Pool, or WHdcat Baum Upper Penn
15. Elevation (Show whether DF, RT, GR, etc.) 3223.5'	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7/3/84: Drilled 11" hole to 4146'. RU & ran 98 jts 8-5/8" 28# & 32# csg & Set @ 4146'. Cemented w/1300 sx Halliburton Lire, 15# salt/sk, 1/4# flocele/sk & 5# gilsonite/sk followed by 200 sx Class "C" w/2% CaCl. PD @ 9: AM 7/3/84 w/1000 psi, increased to 1300 psi. Chk'd float, OK. PU BOP, installed 8-5/8" slips. Cut off csg. WOC 18 hr. NU & tstd BOP to 1000 psi for 30 min, OK. Reduced hole to 7-7/8" and resumed drilling.

Note: Circ'd approx 150 sx cmt to pit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Pat Drexler

TITLE Pat Drexler - Agent

DATE 7/6/84

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT 1 SUPERVISOR

APPROVED BY _____

TITLE _____

DATE

JUL - 9 1984

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUL 9 - 1984

O.C.D.
HOBBS OFFICE