

C CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.O.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name Ferguson	
9. Well No. #1	
10. Field and Pool, or Wildcat Purple Haze	
12. County Lea	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/>	GAS WELL <input type="checkbox"/>	OTHER <input type="checkbox"/>
Name of Operator Anadarko Production Co.		
Address of Operator P. O. Box 806 Eunice, New Mexico 88231		
Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM <u>East</u> THE <u>22</u> LINE, SECTION <u>13S</u> TOWNSHIP <u>38E</u> RANGE <u>38E</u> NMPM.		

15. Elevation (Show whether DF, RT, GR, etc.)

3801.9 GR.

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	
OTHER <u>13 3/8"</u> <input type="checkbox"/>	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

1. MIRURT Spudded 17½" Hole @ 9:30 A.M. 8-6-84.
2. Drilled 17½" hole to 407' @ 1:30 P.M. 8-6-84.
3. Ran Guide shoe & insert float, and 3 centralizers on 11 jts 410' (4 new 13 3/8 48# H-40 ST&C R3 (172')) and (7 used 13 3/8 54.5# K-55 R-3 Buttress csg (238')).
4. RU Halliburton and cemented w/ 425 SX Class "C" w/ 2% CaCL. Plug down @ 5:50 P.M. 8-6-84. Circ 200 SX to pit.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Howard E. Zieck TITLE Field Foreman DATE 9-7-84ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISORTITLE _____ DATE SEP 10 1984

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
SEP 10 1984
O.C.D.
HOBBS OFFICE