

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Fred G. Yates, Inc.		8. Farm or Lease Name Sunburst 9 State Com
3. Address of Operator Sunwest Centre, Suite 919, Roswell, New Mexico 88201		9. Well No. 1
4. Location of Well UNIT LETTER <u>M</u> <u>760</u> FEET FROM THE <u>South</u> LINE AND <u>760</u> FEET FROM THE <u>West</u> LINE, SECTION <u>9</u> TOWNSHIP <u>14S</u> RANGE <u>34E</u> NMPJ		10. Field and Pool, or Wildcat Und E Saunders Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4137.4' GL		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 2:45 PM, July 6, 1984. Drilled 17-1/2" hole to 405'. Set 13-3/8", 54.5#, MRJ casing at 405'. Cemented w/400 sacks Class 'C' cement w/2% CaCl. 75 sacks. cement returns at surface. N.U. BO Equipment. Tested casing & B.O.E. to 500 psig. Held OK. 7/10/84 drilling 11" hole @ 3,322'.

Attached is diagram of Blow out Preventer for Willbros Rig #4 employed on this hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>John R. McMinn</u>	TITLE <u>John R. McMinn - Engineer</u>	DATE <u>8/22/84</u>
APPROVED BY <u>Eddie W. Saxon</u>	TITLE <u>Oil & Gas Inspector</u>	DATE <u>AUG 29 1984</u>
CONDITIONS OF APPROVAL, IF ANY:		