## STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

HG. OF COPIES ACCEIVED	7	
DISTRIBUTION		
SANTA FE	1	
FILE		
U.S.G.S.		
LAND OFFICE		
OFERATOR		

SUDITIONS OF APPROVAL, IF ANY:

## OIL CONSERVATION DIVISION

DISTRIBUTION SANTA FE	P. O. BOX 2088				Form C-103 - Revised 10-1-7		
FILE	SANTA	FE, NEW	MEXICO 87501				
U.S.G.S.					5a. Indicate Ty	pe of Lease	
LAND OFFICE OPERATOR					State X		00
					5. State Oil 6		
SLINDD	V NOTICES AND DES	ACDITE ON	11/71 1 6		LG 2	414 *********	~~~
JUNION THIS FORM FOR PRO USE "MAPPLICAT!	T NUTICES AND KEP POSALS TO DRILL OR TO DEEP ON FOR PERMIT (FORM C-	CHIS UN	WELLS ACK TO A DIFFERENT RESERVO	IR.			
•	The state of the s	TOT FOR SOL	R PROPOSALS.)		7. Unit Agreem	ent Name	7777
OIL X GAB WELL	OTHER.					one realize	
Name of Operator Yates Petroleum Corporation				B. Farm or Lease liame			
. Address of Operator				Chalupa "AAD" State			
207 South 4th St., Ar	tesia, NM 88210		,		9. Well No.	1	
. Location of Well	· · · · · · · · · · · · · · · · · · ·				16 54-14 15	1	
UNIT LEYTER E 23.	10	Month	222		10. Field and F Wildca		t
DHIT LEVYER	FEET FROM THE	NOTER	LINE AND330	. FEET FROM	77777777		rrr
THE West LINE, SECTION 13 TOWNSHIP 14S RANGE 33E NMPM		-					
	TOWNSHI		RANGE JJD	NMPM. [			
	15. Elevation (S)	how whether	DF, RT, GR, etc.)		12. County	74444	444
		4181.3	' GR		Lea		
Check A	ppropriate Box To I	ndicate N	ature of Notice, Repo	ort or Othe	r Data		7777
NOTICE OF IN	TENTION TO:	1	subs	SEQUENT	REPORT OF	·:	
			,				
ERFORM REMEDIAL WORK	PLUG AND A	ANDON	REMEDIAL WORK		ALTE	RING CASING	
EMPORARILY ABANDON ULL OR ALTER CASING			COMMENCE DRILLING OPNS.		PLUG	AND ABANDONM	ENT
	CHANGE PLAN	's []	OTHER Intermedi		· no		F===
OTHER			OTHERTITCETINEGI	ate cas	rug	<del></del>	[X
Describe Proposed or Completed Open work) SEE RULE 1103.	rations (Clearly state all p	ertinent deta	ils, and give pertinent dates	, including c	timated date of	starting any p	roposed
TD 4242! Pag 101 44	-5 0 5/01 00# -						
TD 4242'. Ran 101 jts shoe set 4242'. Float	or 8-5/8" 32# J	-55 casi	ng set 4242'. 1-	Texas Pa	ttern note	ched guid	e
celloseal, 1% CaC12. 1050 psi in 12 hrs. P	Tailed in $w/250$	sx Class	"C" Neat. Compr	essive s	trength of	cement .	<b>-</b> .
1050 psi in 12 hrs. Pand float held okay.	D 11:45 AM 9-10-8	84. Bum	ped plug to 1000	psi, rel	eased pres	sure	
and float held okay. WOC 18 hrs. Nippled up	n and tested to	1 ) SX t	o pit. WOC. Dri	lled out	5:45 AM 9	9-11-84.	
WOC 18 hrs. Nippled upon the Drilled plug and resum		LUUU# IO	r 30 minutes, OK.	Reduced	hole to 7	7-7/8".	
_							
•							
I hereby certify that the information ab	ove is true and complete to	the best of	my knowledge and belief.				
- J							
Vijanita Nood	Lu .	ITLE Pro	duction Superviso	r	DATE 9-1	2-84	
		w			DATE	<u>04</u>	
ORIGINAL SIGNED BY JE			•		ÇFI	1 4 19	ΩΛ
DISTRICT I SUPER	MISOR +	!TLE			DATE OLI	TII	U <del>T</del>

RECEIVED

SEP 1 3 1984

O C.O. HOBBE COMCE