

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
T. Rustler	2050	T. Canyon Shale	11502	T. Ojo Alamo		T. Penn. "B"	
T. Anhy		T. Strawn Lime	11900	T. Kirtland-Fruitland		T. Penn. "C"	
T. Salt		T. Atoka	12438	T. Pictured Cliffs		T. Penn. "D"	
T. Salt		T. Miss		T. Cliff House		T. Leadville	
T. Yates	3080	T. Devonian		T. Menefee		T. Madison	
T. 7 Rivers	3255	T. Silurian		T. Point Lookout		T. Elbert	
T. Queen	3902	T. Montoya		T. Mancos		T. McCracken	
T. Grayburg		T. Simpson		T. Gallup		T. Ignacio Qtzite	
T. San Andres	4622	T. McKee		T. Base Greenhorn		T. Granite	
T. Glorieta	6130	T. Ellenburger		T. Dakota		T.	
T. Paddock		T. Gr. Wash		T. Morrison		T.	
T. Blinbry		T. Granite		T. Todillo		T.	
T. Tubb	7451	T. Delaware Sand		T. Entrada		T. Morrow Lime	13086
T. Drinkard		T. Bone Springs		T. Wingate		T. Barnett Shale	13405
T. Abo	8200	T. Lwr Strwn Mkr	12190	T. Chinle		T. Austin	13501
T. Wolfcamp Lm	9834	T. XX Marker	10046	T. Permian		T.	
T. Penn. BASAL		T. Virgilian	10662	T. Penn. "A"		T.	
T. Cisco (Bough C)	10940						

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
No. 2, from.....to.....feet.....
No. 3, from.....to.....feet.....
No. 4, from.....to.....feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	373	373	Surface, Redbeds	9420	9820	400	Dolomite
373	1482	1109	Anhy, Redbeds	9820	9920	100	Limestone, Dolo
1482	2106	624	Anhy, Redbeds, Salt	9920	10190	270	Lime
2106	3597	1491	Anhy, Salt	10190	11288	1098	Lime, Cht, Shale
3597	4594	997	Anhy, Dolo	11288	11688	400	Lime, Shale, Dolo
4594	4640	46	Anhy, Dolo, Shale	11688	11900	212	Shale, Lime, Sand, Cht
4640	5060	420	Dolo, Anhr	11900	13012	1112	Lime, Shale, Sand
5060	5930	870	Dolo	13012	13710	698	Shale, Lime
5930	6290	360	Dolo, Limestone				
6290	6520	230	Dolo, Anhy				
6520	8170	1650	Dolo, Tr. Cht				
8170	8870	700	Dolo, Anhy, Shale				
8870	9070	200	Dolo, Lime, Shale				
9070	9420	350	Dolo, Limestone, Anhy				