

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State ☐	Fee ☒
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Firm or Lease Name Woodward "ABD"	
9. Well No. 1	
10. Field and Pool, or Wildcat Undesignated	
12. County Lea	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER-

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
207 South 4th St., Artesia, NM 88210

4. Location of Well
UNIT LETTER G 1980 FEET FROM THE North LINE AND 1980 FEET FROM
THE East LINE, SECTION 24 TOWNSHIP 14S RANGE 35E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3983.9' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	OTHER <u>Production Casing</u> ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

TD 13710'. Ran 344 jts 5-1/2" casing as follows: 108 jts 17# S-95; 177 jts 17# N-80; 36 jts 17# S-95 and 23 jts 20# N-80, casing set 13710'. Float shoe set 13710'. Float collar set 13664'. DV tool set 13116'. Cemented 1st stage as follows: 125 sx TLW (yield 1.81) + .75% TF-4. Tailed in w/125 sx Class "H" (yield 1.24) + 18% salt + 5% Thixad + .7% CF-9 + .5% TF-4 + .1% WR-2. PD 12:30 AM 4-25-85. Opened DV tool and circulated for 6 hrs. Stage 2: Cemented w/125 sx TLW (yield 1.81) + .75% TF-4. Tailed in w/920 sx Class "H" (yield 1.24) + 18% salt + 5% Thixad + .7% CF-9 + .5% TF-4 + .2% WR-2. PD 8:15 AM 4-25-85. Bumped plug to 1000 psi, held okay. Circulated 50 sx to pit. WOC 18 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Juanita Bonilla TITLE Production Supervisor DATE 4-30-85
APPROVED BY ORIGINAL SIGNED BY CODE SEAY TITLE OIL & GAS INSPECTOR DATE MAY 6 1985
CONDITIONS OF APPROVAL, IF ANY: