

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
Rustler 1762							
T. Anhy		T. Canyon		T. Ojo Alamo		T. Penn. "B"	
T. Salt		T. Strawn		T. Kirtland-Fruitland		T. Penn. "C"	
B. Salt	2612	T. Atoka		T. Pictured Cliffs		T. Penn. "D"	
T. Yates	2723	T. Miss		T. Cliff House		T. Leadville	
T. 7 Rivers		T. Devonian		T. Menefee		T. Madison	
T. Queen	3498	T. Silurian		T. Point Lookout		T. Elbert	
T. Grayburg		T. Montoya		T. Mancos		T. McCracken	
T. San Andres	4182	T. Simpson		T. Gallup		T. Ignacio Qtzte	
T. Glorieta	5660	T. McKee		Base Greenhorn		T. Granite	
T. Paddock		T. Ellenburger		T. Dakota		T.	
T. Elinebry		T. Gr. Wash		T. Morrison		T.	
T. Tubb	7082	T. Granite		T. Todilto		T.	
T. Drinkard		T. Delaware Sand		T. Entrada		T.	
T. Abo	7812	T. Bone Springs		T. Wingate		T.	
T. Wolfcamp Lm	9220	T. XX Marker	9446	T. Chinle		T.	
T. Penn.		T. Virgilian	9840	T. Permian		T.	
T. Cisco (Bough C)		T.		T. Penn. "A"		T.	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
No. 2, from.....to.....feet.....
No. 3, from.....to.....feet.....
No. 4, from.....to.....feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1625	1625	Surface, Redbeds	9040	9160	120	Dolomite, Shale
1625	2150	525	Redbeds, Anhydrite	9160	9760	600	Lime, Dolo, Chert, Shale
2150	2620	470	Redbeds, Salt	9760	10197	437	Lime, Shale
2620	3890	1270	Salt, Anhydrite				
3890	4100	210	Anhydrite				
4100	4250	150	Anhy, Dolo, Shale, Lime				
4250	4600	350	Dolomite				
4600	4880	280	Dolomite, Anhydrite, Sand				
4880	5200	320	Dolo, Chert, Shale, Lime				
5200	5640	440	Dolomite, Lime				
5640	5880	240	Lime, Dolo, Anhy, Shale, Sd.				
5880	7344	1464	Dolo, Anhy, Shale, Sd				
7344	7790	446	Dolo, Anhydrite				
7790	9040	1250	Dolo, Shale, Anhydrite				

RECEIVED

MAR 14 1985

U.S. DEPT. OF JUSTICE
HONORARY OFFICE