

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Rustler 1738	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Anhy	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
T. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
B. Salt	T. Miss	T. Cliff House	T. Leadville
T. Yates 2666	T. Devonian	T. Menefee	T. Madison
T. 7 Rivers	T. Silurian	T. Point Lookout	T. Elbert
T. Queen 3424	T. Montoya	T. Mancos	T. McCracken
T. Grayburg	T. Simpson	T. Gallup	T. Ignacio Qtzte
T. San Andres 4134	T. McKee	Base Greenhorn	T. Granite
T. Glorieta 5576	T. Ellenburger	T. Dakota	T.
T. Paddock	T. Gr. Wash	T. Morrison	T.
T. Blinbry	T. Granite	T. Todilto	T.
T. Tubb 7000	T. Delaware Sand	T. Entrada	T.
T. Drinkard	T. Bone Springs	T. Wingate	T.
T. Abo 7732	T. XX Marker 9336	T. Chinle	T.
T. Wolfcamp LS 9126	T. Virgilian 9762	T. Permian	T.
T. Penn.	T. Bough C 9866	T. Penn. "A"	T.
T. Cisco (Bough C)			

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
No. 2, from.....to.....feet.....
No. 3, from.....to.....feet.....
No. 4, from.....to.....feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	455	455	Sandy Red Rock, Surface				
455	1166	711	Redbeds				
1166	1766	600	Redbeds, Anhydrite,				
1766	2269	503	Anhydrite, Salt				
2269	3779	1510	Anhydrite, Redbeds				
3779	4320	541	Anhydrite, Shale				
4320	4420	100	Dolomite				
4420	5200	780	Dolomite, Shale				
5200	5584	384	Dolomite, Lime, Shale, Anhy.				
5584	6980	1396	Anhy, Dolo, Sand, Shale				
6980	9140	2160	Dolo, Sand, Anhydrite				
9140	9348	208	Lime, Cht, Dolo, Shale				
9348	9666	318	Lime, Shale, Cht				
9666	10145	479	Lime, Shale				

RECEIVED

SEP 11 1985

O.C.D.
HOBBS OFFICE