

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

3a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
3. State Oil & Gas Lease No. LG 2359

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator
Yates Petroleum Corporation

Address of Operator
207 S. 4th St., Artesia, NM 88210

Location of Well
UNIT LETTER L 1980 FEET FROM THE South LINE AND 330 FEET FROM
West 12 TOWNSHIP 14S RANGE 33E NMPM.

7. Unit Agreement Name
8. Farm or Lease Name Harris AAU State
9. Well No. 2
10. Field and Pool, or wildcat Und. Saunders Permo Upper Penn
11. Elevation (Show whether DF, RT, CR, etc.) 4191' GR
12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
WILL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER Perforate, Treat <input checked="" type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8-13-85. TD 10145'. POOH w/rods and pump.
8-14-85. Squeezed perfs 10015-39' to 3000# w/85 sx cement. WIH and perforated 9890-9913' w/10 .50" holes as follows: 9890, 91, 92, 93, 98, 99, 9900, 11, 12 and 13'.
8-15-85. Acidized perfs 9890-9913' w/2500 gals 15% NEFE acid and 15 ball sealers.
8-22-85. Re-acidized perfs 9890-9913/ w/6000 gals pad, 12000 gals 20% Retarded acid.
8-26-85. WIH and perforated 9770-9822' w/10 .50" holes as follows: 9770, 71, 72, 87, 88, 89, 90, 9820, 21 and 22'.
8-28-85. Acidized perfs 9770-9822' w/2500 gals 15% NEFE acid + 16 ball sealers.

Perforations open 9890-9913' and 9770-9822'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Jerry Sexton
ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT 1 SUPERVISOR

TITLE Production Supervisor

DATE 8-29-85

COPIES BY
CONDITIONS OF APPROVAL, IF ANY:

SEP - 9 1985

RECEIVED

AUG 30 1985

O.C.D.
HOBBS OFFICE