INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or despended well. It shall be accomputed by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

_	_	Southeas	tern	New Mexico		Nor	thwestem Ne	w Mexico
	stler Anhy	1720	т.	Canyon	T.	Ojo Alamo	т.	Penn. "B"
т.	Salt		. T.	Strawn	т.	Kirtland-Fruitland	Т.	Penn. "C"
				Atoka				
	Yates			Miss				
т.	7 Rivers		. т.	Devonian	Т.	Menefee	T.	Madison
	Queen	3496	. т.	Siluri an	т.	Point Lookout	Т.	Elbert
	Grayburg			Montoya				
	San Andres	4190	. т.	Simpson	Т.	Gallup		Ignacio Qtzte
	Glorieta	5674	. т.	McKee	Bas	e Greenhorn		Granite
т.	Paddock			Ellenburger				
			т.	Gr. Wash	Т.	Morrison	T.	
т.	Tubb	7092	. т.	Granite	Т.	Todilto	Т.	····
т.	Drinkard		. Т.	Delaware Sand	Т.	Entrada	T.	······································
т.	Аьо	7800	. T.	Bone Springs	т.	Wingate	T.	
Ť.	Wolfcamp LS	9240	. т.	XX Marker 9464	Т.	Chinle	т.	<u></u>
т.	Penn		. T.	Virgilian 9896	Т.	Permian	T.	******
т	Cisco (Bough C)		. т.	Bough C 9993	Т.	Penn. "A"	Т.	
				OIL OR GAS	SÅ	NDS OR ZONES		
No.	1, from			_10				to
No.	2, from			.10	No	. 5, from		to
No.	3, from			_to	No	. 6, from	*******	to

IMPORTANT WATER SANDS

No. 1, from		feet,	
No. 2, Iroin	<u></u> toto	fcct.	4 • • • • • • • • • • • • • • • • • • •
No. 3, from			42 *** * * * * * * * * * * * * * * * * *
No. 4 from	•	faat	

Include data on rate of water inflow and elevation to which water rose in hole.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	465	465	Surface, Redbeds				
465	2159	1694	Redbeds				
2159	2648	489	Redbeds, Dolo, Anhy		1		
2648	2792	144	Salt, Dolo		1		
2792	4050	1258	Anhydrite				
4050	4540	490	Dolo, Anhy				
4540	5230	690	Dolo				
5230	5680	450	Limestone, Dolo				
5680	5880	200	Anhy, Dolo, Sand				
5880	6210	330	Anhy, Dolo				
6210	6330	120	Dolo, Cht, Shale, Sand				
6330	6980	650	Dolo				
6980	7410	430	Dolo, Sand				· · ·
7410	7670	260	Dolomite				·
7670	9220	1550	Shale, Anhy, Dolo				
9220	9880	660	Limestone, Dolo, Cht				
0880	10209		Limestone, Shale			1	