STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

40. 07 (0*158 06661+40		
DISTRIBUTION	7	i
SANTA FE	1	
FILE		
U.S.G.S.	1	
LAND OFFICE	1.	
OPERATOR		

OIL CONSERVATION DIVISION

DISTRIBUTION	P. O. BOX 2088	•	Form C-103	
SANTA FE	SANTA FE, NEW MEX: CO 87501		Revised 10-1-78	
FILE		Sa. Indicate Type o	of Lease	
U.1.0.8,		State X	F•• 🗍	
LAND OFFICE				
OPERATOR		5, State Oil & Gas	Lease No.	
		NM_V-1	NM V-124	
SUNDR	Y NOTICES AND REPORTS ON WELLS			
USE "PRICATI	ION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	_7/////////////////////////////////////		
1. on [] * saa []	•	7. Unit Agreement	Name	
well XI well 2. Name of Operator	OTHER-		6 5	
	,		8. Farm or Lease Name	
MWJ PRODUCIN	NG COMPANY		Baum 17 State	
3. Address of Operator		9. Well No.	i	
	nois - Suite 1100 Midland, Texas 79701	2		
(, Location of Well		10. Field and Pool, or Wildcat		
UNIT LETTER H 19	980 PEET FROM THE North LINE AND 660 PEET FR	Baum Upper Penn		
East LINE, SECTION	TOWNSHIP 14S RANGE 33E NAME	(
- Cinc, section	TOWNSHIP RANGE RANGE	(
mmmm	15. Elevation (Show whether DF, RT, GR, etc.)	12. County		
	4235' GL	Lea		
<u>, , , , , , , , , , , , , , , , , , , </u>			<i></i>	
	Appropriate Box To Indicate Nature of Notice, Report or (Other Data		
NOTICE OF IN	TENTION TO: SUBSEQUE	NT REPORT OF:		
			<u></u>	
PERFORM REMEDIAL WORK	PLUE AND ABANDON REMEDIAL WORK	ALTERIN	G CASING	
TEMPORARILY ABANDON	COMMENCE DRILLING OPHS.	PLUG AND	ABANDONMENT	
PULL OR ALTER CABING	CHANGE PLANS CASING TEST AND CEMENT JOS			
	OTHER			
OTHER				
	prations (Clearly state all pertinent details, and give pertinent dates, includi	ng estimated date of sto	arting any proposed	
work) SEE RULE 1103.		•		
Casing Record: 1	13-3/8" @ 415' (circulated cement)	•		
	3-5/8" @ 4115' (Circulated cement)			
	5-1/2" @ 10,150' (Top of cement @ 8700')			
P	Perforations from 9923-9950'			
	·	•		
Proposed Plugging				
1. CIBP & 35' ce	ement on top @ 9800'			
Shoot off and	l pull approx 6000' of 5-1/2" casing			
3. 100' cement f	from 5950' to 6050' (5-1/2" stub-in and out plu	g) - need to to	a o	
4. 100' cement f	from 4065' to 4165' (need to tag)	B) co c.	~ 8	
	from 1600' to 1700'			
	at surface & install dry hole marker			
Note: Mud betwee	en plugs, 25# saltgel per bbl wtr)			
	•			
I handly continue the information of	bove is true and complete to the best of my knowledge and belief.			
The state of the s	1			