

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" FORM C-101 FOR SUCH PROPOSALS.

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name ---
2. Name of Operator Exxon Corp.	8. Farm or Lease Name James Reed McCrory
3. Address of Operator P. O. Box 1600, Midland, TX 79702	9. Well No. 1
4. Location of Well UNIT LETTER <u>J</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>15</u> TOWNSHIP <u>13S</u> RANGE <u>34E</u> NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4144' GR	12. County Lea

10. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1702.

Spud 17-1/2" hole on 8-31-85. Set 13-3/8", K55 STC at 406'. Cemented w/450 sx ClC. Circulate to surface. Tested csg. to 300 & 1500# - OK. Waited 36 hours on cement before drilling. Set 8-5/8" K55 at 4300'. Cemented w/2400 sx ClC. Circulated to surface. Tested csg. to 1500 psi - OK. Waited 26-1/2 hours before drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Melba Kripling TITLE Unit Head DATE Oct. 9, 1985

ORIGINAL SIGNED BY JERRY SEKTON
DISTRICT 1 SUPERVISOR

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE OCT 11 1985

RECEIVED
OCT 10 1985
D.C.D.
HOBBS OFFICE