

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Firm or Lease Name	
Elkan A	
9. Well No.	
1	
10. Field and Pool, or Wildcat	
Wildcat	
12. County	
Lea	

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator
Cities Service Oil and Gas Corporation
3. Address of Operator
P.O. Box 1919 - Midland, Texas 79702
4. Location of Well
UNIT LETTER <u>L</u> <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM THE <u>West</u> LINE, SECTION <u>25</u> TOWNSHIP <u>13S</u> RANGE <u>34E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)
4111' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 378' Surface Rock. Prep to drill ahead. MIRU a rotary and spudded a 17-1/2" hole @ 1130 MDT on 10-21-85 and drilled to a T.D. of 378' in Surface Rock. Ran and set 10 jts. (160.59') of 13-3/8" OD 48# casing @ 378' and cemented w/400 sacks of Class C + 2% CaCl<sub>2</sub> & 0.25# Celloflake/sack cement. PD @ 0200 MDT on 10-22-85. Circulated 200 sacks of cement to the surface. WOC 18 hrs. Tested 13-3/8" OD casing to 600# for 30 min. - OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Elmer Startz</u>	TITLE <u>Reg. Opr. Mgr. - Prod.</u>	DATE <u>10-23-85</u>
APPROVED BY <u>ORIGINAL SIGNED BY JERRY SEXTON</u>		
DISTRICT 1 SUPERVISOR		
CONDITIONS OF APPROVAL, IF ANY:		

OCT 25 1985