STATE OF NEW MEXIC	CO						グバークス	25 - 2014	97	
ENERGY AND MINERALS DEPA			CONSERVAT	TION DIVI	1012		Form C-10		/)	
							Revised 10-1-78			
DISTRIBUTION SANTA FE, NEW MEXICO 87501							5A. Indicate Type of Lease			
SANTA FE FILE							STATE X PEE			
U.S.G.S.							5, State Oil & Gas Lease No.			
LAND OFFICE							E-2426			
OPERATOR		= ==								
APPLICATIO	IN FOR PER	MIT TO	DRILL, DEEPEN	I, OR PLUG B	BACK				7777	
	_						7. Unit Agr	eement Name		
b. Type of Well PLUG BACK								8. Farm or Lease Name		
OIL SAS WELL		SINGLE MULTIPLE ZONE			Amerada-State					
2. Name of Operator	ОТНЕЯ	· · · · · · · · · · · · · · · · · · ·		10NE 4		SONE [9. Well No.			
TEXACO Inc.							1			
3. Address of Operator								10. Field and Pool, or Wildcat		
								azy J. Penn Limestone		
4. Location of Well								THE		
AND 330 PEET FROM	THE West	LIN	t or sec. 2	TWP. 14-S	AGE. 33	-E	XXXXXXX	(1)	444	
	1111111						12. County		M	
							Lea		7]]]	
	/////////								1111	
	7777777	77777			77777	777777			IIII	
				19. Proposed De	epth	19A. Formation Limesto		Rotary	:	
el. Elevations (show whether DF,				· · · · · · · · · · · · · · · · · · ·				I		
4200' GR.	et	Status Plug. Bond 21B. Drilling Contractor			November 11, 1985					
23.							J	· · · · · · · · · · · · · · · · · · ·		
23.		. P	ROPOSED CASING A	ND CEMENT PRO	GRAM					
SIZE OF HOLE	SIZE OF C	ASING	WEIGHT PER FOO	TESTING	DEBTU	I CACKE OF	CEMENT	F. T. T.		
15"	11-3/4"	ASING	42#	SETTING DEPTH		SACKS OF CEMENT		EST. TO Circulate		
12-1/4"	8-5/8*		28# - 1240			2000		Circulate		
22 2/ 1	, - , , , , ,		24# - 2920		1 1					
7-7/8"	5-1/2"		17#			2150		Circulate		
, -	-, -			•						
Cementing Program										
Surface Casing:	1700 sxs	Class	s "H" with 2	% CaCl (15.6 p	pg, 1.1	8 cu.f	t./sx.).		
_										
Intermediate Casing: 1800 sxs Light Weight with 15# salt and 1/4# flocele										
(12.7 ppg, 2.1 cu			.lowed by 20	00 sxs Cla	ass "F	" with	1/4# f	locele		
(15.6 ppg, 1.18 d	cu.ft./s:	x.).								
Production Casin										
ppg, 2.00 cu.ft.,	/sx.) for	llowed	d by 200 sxs	50/50 Po	ozmix	Class "	H" wit	h 1/4#		
flocele and 0.8%	HALAD-9	(13.6)	ppg, 1.4 c	u.ft./sx	•)•			.		
2ND STAGE - 1200 sxs Light Weight with 1/4# flocele (12.3 ppg, 2.00 cu.ft./sx.).										
DV tool at 7000'	•									
N ABOVE SPACE DESCRIBE PR	OPOSED PROG	RAM: IF P	ROPOSAL 18 TO DEEPEN	OR PLUE BACK, 61	VE DATA OI	PRESENT PRO	DUCTIVE ZONE	AND PROPOSED NEW	PRODU	
hereby certify that the information	on above is true	and comp	lete to the best of my	knowledge and be	illef.					
1114	1 -	- F		Baker, II	-					
igned VVVI Va	Kert		Tule Dist. I		Ma na go	ert	ate	4-85		
(This space for :	State Use i				Y				-	
		Y SEXTOI	N					4000		
ORIGINAL SIGNED BY JERRY SEXTON PROVED BY DISTRICT I SUPERVISOR TITLE							NOV 5 - 1985			
PPROVED BY		~~~	111 L E				ATE			