

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Cities Service Oil and Gas Corporation	8. Farm or Lease Name State DX
3. Address of Operator P.O. Box 1919 - Midland, Texas 79702	9. Well No. 1
4. Location of Well UNIT LETTER <u>H</u> 1980 FEET FROM THE <u>North</u> LINE AND 660 FEET FROM THE <u>East</u> LINE, SECTION <u>29</u> TOWNSHIP <u>14S</u> RANGE <u>33E</u> NMPM.	10. Field and Pool, or Wildcat Undesignated Permo Upper Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4221' GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 412' Surface Rock & Red Beds. Prep to drill ahead. MIRU a rotary and spudded a 17-1/2" hole @ 1130 MST on 12-08-85 and drilled to a T.D. of 412' in Surface Rock & Red Beds. Ran and set 11 jts. (397.01') of 13-3/8" OD 48# casing @ 412' and cemented w/400 sacks of Class C + 2% CaCl₂ + 0.25# Flocele/sack cement. PD @ 2130 MST on 12-08-85. Circulated 20 sacks of cement to the surface. WOC 18 hrs. Tested 13-3/8" OD casing to 600# for 30 min. - OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. Mer Startz TITLE Reg. Opr. Mgr. - Prod. DATE 12-10-85

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON TITLE DISTRICT SUPERVISOR DATE DEC 16 1985

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
DEC 13 1985
P.C.D.
HARRIS OFFICE