

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR
Coastal Oil & Gas Corp.

3. ADDRESS OF OPERATOR
P. O. Box 235, Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: F 1980' FNL & 1892' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: 10,010'

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>

(other) Set 13 3/8", 8 5/8" & 5 1/2" csg.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-21-85 - Spud 11-21-85
11-22-85 RU & ran 10 jts. 13 3/8" csg. Circ. cmt. w/425 sks. Class "C"
w/CaCl₂ Circ. 125 sks. PD 9:15 PM WOC Cut off WOC & NU.
11-28-85 RU & ran 95 jts. 8 5/8" csg. 32# & 24# K-55 csg. Shoe @ 4079'.
RU Howco cmt. w/1450 Howco lt. wt. w/7# salt. Tail w/250 sks. Class "C"
PD 11:30 PM Circ. 250 sks. WOC NU BOP. Set slips Install "B" Sec. test
to 1000 psi.
12-14-85 Ran 244 jts. 5 1/2" csg. 17# N-80, S-95, & K-55 LT&C, 8 centralizers used
@ 10,010' FC @ 9960.66' Cmt./380 sks. Class "H" 5050 poz w/5# salt 2%
gel 6% Holad 9 14.45 ppg. 1.29 yield Est. TOC 8500'. PD @ 8:45 PM ND
Cut off NU "C" Sec. Clean pits. Rig released 2 AM 12-14-85.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Joe Vanderford TITLE Operations Analyst DATE 1-23-86

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:
ACCEPTED FOR RECORD

JAN 27 1986

*See Instructions on Reverse Side

RECEIVED
FEB - 3 1968
HON. J. EDGAR HOOVER
FEDERAL BUREAU OF INVESTIGATION
U. S. DEPARTMENT OF JUSTICE