

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG 3818	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Pyro ABK State
3. Address of Operator 207 South 4th St., Artesia, NM 88210		9. Well No. 2
4. Location of Well UNIT LETTER <u>C</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>2310</u> FEET FROM THE <u>West</u> LINE, SECTION <u>33</u> TOWNSHIP <u>13S</u> RANGE <u>33E</u> NMPM.		10. Field and Pool, or Wildcat Lazy J Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4247.5' GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☒ Production Casing, Perforate, Treat

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 10100'. Ran 247 jts 5-1/2" casing as follows: 79 jts 20# N-80, 93 jts 17# J-55; 72 jts 17# N-80 and 3 jts 20# N-80 (total 10100') casing, set at 10100'. 1-Regular Guide shoe set 10100'. Float collar set at 10060'. Cemented w/1170 sx Class "H" w/.7% CF-14 + .4% TF-4. PD 5:00 AM 1-23-86. Bumped plug to 2500# for 30 minutes, released pressure, float and casing held okay. WOC. WOCU 3 days. Perforated 9843-48' w/10 .50" holes (2 SPF). Acidized perms 9843-48' w/3500 gals 15% NEFE acid plus 10 ball sealers.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Production Supervisor DATE 2-6-86

ORIGINAL SIGNED BY JERRY TEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE FEB 10 1986

CONDITIONS OF APPROVAL, IF ANY: