

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Cities Service Oil & Gas Corp.		8. Farm or Lease Name Elkan A
3. Address of Operator P.O. Box 1919 - Midland, Texas 79702		9. Well No. 2
4. Location of Well UNIT LETTER <u>E</u> <u>2310</u> FEET FROM THE <u>North</u> LINE AND <u>990</u> FEET FROM THE <u>West</u> LINE, SECTION <u>25</u> TOWNSHIP <u>13S</u> RANGE <u>34E</u> NMPM.		10. Field and Pool, or Wildcat Undesgn. Alston Ranch Upper Pennsylvanian
15. Elevation (Show whether DF, RT, GR, etc.) 4116' GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 380' Red Beds & Surface Rock. Prep to drill ahead. MIRU a rotary and spudded a 17-1/2" hole @ 0530 MST on 11-13-86 and drilled to a T.D. of 380' in Red Beds and Surface Rock. Ran and set 10 jts. (362.50') of 13-3/8" OD 48# casing @ 376' and cemented w/400 sacks of Class C + 2% CaCl & 0.25# Celophane Flakes/sack cement. PD @ 2037 MST on 11-13-86. Circulated 72 sacks of cement to the surface. WOC 18 hrs. Tested the 13-3/8" OD casing to 800# for 30 min. - OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Elmer Startz TITLE Reg. Opr. Mgr. - Prod. DATE 11-17-86

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT 1 SUPERVISOR TITLE DATE NOV 19 1986

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
NOV 18 1986
HCSIS Office