

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>	
5. State Oil & Gas Lease No. E-8087	
7. Unit Agreement Name	
8. Farm or Lease Name Mesa AAF State	
9. Well No. 1	
10. Field and Pool, or WHdcat Unid. Lazy J	
12. County Lea	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation
3. Address of Operator 105 South 4th St., Artesia, NM 88210
4. Location of Well UNIT LETTER M 990 FEET FROM THE South LINE AND 990 FEET FROM THE West LINE, SECTION 28 TOWNSHIP 13S RANGE 33E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4246.5' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER Production Casing <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

TD 10100'. Ran 244 jts 5-1/2" casing as follows: 37 jts 5-1/2" 20# N-80, 45 jts 5-1/2" 20# N-80, 90 jts 5-1/2" 17# J-55, 69 jts 5-1/2" 17# N-80 and 3 jts 5-1/2" 20# N-80, casing set 10100'. 1-Regular guide shoe set 10100' and float collar set 10061'. Cemented w/675 sx Class "H" w/.7% CF-14 and .4% TF-4 (yield 1.18, weight 15.6). PD 4:00 PM 2-4-87. Bumped plug to 2000 psi, released pressure and float and casing held okay. WOC.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Jerry Sexton

TITLE Production Supervisor

DATE 2-10-87

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT 1 SUPERVISOR

TITLE

DATE FEB 13 1987

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
FEB 12 1987
OCD
HOBBS OFFICE