

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Cities Service Oil & Gas Corp.		8. Farm or Lease Name Yates A
3. Address of Operator P.O. Box 1919 - Midland, Texas 79702		9. Well No. 1
4. Location of Well UNIT LETTER <u>H</u> <u>1880</u> FEET FROM THE <u>North</u> LINE AND <u>760</u> FEET FROM THE <u>East</u> LINE, SECTION <u>26</u> TOWNSHIP <u>13S</u> RANGE <u>34E</u> NMPM.		10. Field and Pool, or Wildcat Undesign. Alston Ranch Upper Pennsylvanian
15. Elevation (Show whether DF, RT, GR, etc.) 4119' GR		12. County Lea

### Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 4303' Anhydrite. Prep to drill ahead. Drilled a 11" hole from 377' to a T.D. of 4303' in Anhydrite. Ran and set 52 jts.(2179.83') of 8-5/8"OD 24# and 49 jts.(2107.42') of 8-5/8" OD 32# casing @ 4302' and cemented w/1600 sacks of TLW + 15# salt, 5# Gilsonite & 9.25# Cello-flake/sack + 300 sacks of Class C + 3# salt/sack cement. PD @ 1015 MST on 2-28-87. Circulated 200 sacks of cement to the surface. WOC 18 hrs. Tested the 8-5/8"OD casing to 800# for 30 min. - OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. A. Vitano TITLE Dist. Opr. Mgr. - Prod. DATE 3-02-87

ORIGINAL SIGNED BY JERRY SEXTON  
APPROVED BY DISTRICT SUPERVISOR TITLE  DATE MAR 4 1987

CONDITIONS OF APPROVAL, IF ANY: