

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-101
Effective 1-1-65

SUMMARY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR THE REPORTING OF A WELL WHICH IS A DIFFERENT RESERVATION, OR FOR THE REPORTING OF A WELL WHICH IS A DIFFERENT RESERVATION.)		5a. Indicate Type of Lease State ☐ Fee ☒
1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER		5. State Oil & Gas Lease No.
2. Name of Operator AMERADA HESS CORPORATION		7. Unit Agreement No.
3. Address of Operator DRILLING SERVICES, P. O. BOX 2040, TULSA OKLAHOMA 74102		8. Field or Lease Name MADDUX
4. Location of Well UNIT LETTER <u>M</u> <u>660</u> FEET FROM THE <u>SOUTH</u> LINE AND <u>660</u> FEET FROM THE <u>WEST</u> LINE, SECTION <u>11</u> TOWNSHIP <u>13S</u> RANGE <u>38E</u> N.M.P.M.		9. Well No. <u>1</u>
11. Elevation (Show whether DT, HT, GR, etc.) <u>3794 GR</u>		10. Field and Pool, or Wellset BRONCO SILURO-DEVONIAN
		12. County LEA

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER ☐	SUBSEQUENT REPORT OF: PLUG AND ABANDON ☐ CHANGE PLANS ☐ OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3/7/88--RAN 106 JT 9-5/8" 36# S-80 & K-55 R3 'A' CASING WIHT SHOE @ 4630'. CEMENTED 9-5/8" CASING WITH 1115 SX CLASS 'C' LITE WITH ADDITIVES, YIELD 2.64 CU FT/SX, SW=12.0 PPG. TAILED IN WITH 200 SX CLASS 'C' WITH ADDITIVES, YIELD 1.32 CU FT/SX, SW=1.32 CU FT/SX. CIRCULATED 6 BBL (13 SX) CEMENT TO SURFACE. BUMPED PLUG 10:45 PM 3/7/88.

3/9/88--TESTED PIPE RAMS, CHOKE MANIFOLD, ALL MUD LINES AND BLIND RAMS TO 3000 PSI WITH RIG PUMPS. TESTED ANNULAR PREVENTERS TO 1500 PSI, ALL TESTED OK. TEST CASING TO 1200 PSI, OK. TAGGED CEMENT @ 4533', DRILLED CEMENT, WIPER PLUG, FLOAT COLLAR AND 40' OF FIRM CMT, TESTED CASING TO 1000 PSI, OK. DRILLED FLOAT SHOE @ 4630' AND STARTED DRILLING FORMATION FROM 4630'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. R. WILSON *JR Wilson* TITLE SUPERVISOR DRLG ADMIN SVS. DATE 3/9/88

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON TITLE DISTRICT 1 SUPERVISOR DATE 3/9/88

CONDITIONS OF APPROVAL, IF ANY: