




Halliburton Reservoir Evaluation System



HALLIBURTON SERVICES

Duncan, Oklahoma 73536



A Halliburton Company

NOMENCLATURE

B	= Formation Volume Factor	(Res Vol/Std Vol)
c_t	= System Total Compressibility	(Vol/Vol)/psi
DR	= Damage Ratio	
h	= Estimated Net Pay Thickness	Ft
k	= Permeability	md
m	{ (Liquid) Slope Extrapolated Pressure Plot (Gas) Slope Extrapolated m(P) Plot	psi/cycle MM psi ² /cp/cycle
m(P*)	= Real Gas Potential at P*	MM psi ² /cp
m(P _f)	= Real Gas Potential at P _f	MM psi ² /cp
AOF ₁	= Maximum Indicated Absolute Open Flow at Test Conditions	MCFD
AOF ₂	= Minimum Indicated Absolute Open Flow at Test Conditions	MCFD
P*	= Extrapolated Static Pressure	Psig
P _f	= Final Flow Pressure	Psig
Q	= Liquid Production Rate During Test	BPD
Q ₁	= Theoretical Liquid Production w/Damage Removed	BPD
Q _g	= Measured Gas Production Rate	MCFD
r _i	= Approximate Radius of Investigation	Ft
r _w	= Radius of Well Bore	Ft
S	= Skin Factor	
t	= Total Flow Time Previous to Closed-in	Minutes
Δt	= Closed-in Time at Data Point	Minutes
T	= Temperature Rankine	°R
φ	= Porosity (fraction)	
μ	= Viscosity of Gas or Liquid	cp
Log	= Common Log	