

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>	
5. State Oil & Gas Lease No. LG-2265	
7. Unit Agreement Name	
8. Farm or Lease Name Tahoe WA State	
9. Well No. 2	
10. Field and Pool, or Wildcat Saunders Permian Upper Penn.	
12. County Lea	

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Tahoe Energy, Inc.
3. Address of Operator 4402 West Industrial - Midland, Texas 79703
4. Location of Well UNIT LETTER <u>E</u> , <u>1650</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>11</u> TOWNSHIP <u>14S</u> RANGE <u>33E</u> NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)  
4199.6 Gr.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

- Spudded well @ 6:45 a.m. (MST) on 3-27-88, with 17 1/2" hole.
- Drilled and set casing @ 383', with 5 centralizers. Ran 10 joints of 13 3/8" casing, 48#, STC.
- The Western Company cemented w/380 sx of class "c" + 2% CaCl.
- Circulated 46 sx of cement to surface.
- Plug down @ 2:17 p.m. (MST) on 3-27-88.
- 14 hours WOC and nippleing up.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

APPROVED (X) J. A. Greenman TITLE President DATE 3-29-88  
ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT I SUPERVISOR  
APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE MAR 31 1988  
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED  
MAR 30 1988  
HOBBS OFFICE  
OCCD