

COPIES RECEIVED		
DISTRIBUTION		
SAFE		
S.		
OFFICE		
ATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator
Maralo, Inc.

3. Address of Operator
P. O. Box 832, Midland, Texas 79702 0832

4. Location of Well
Section E 1980 FEET FROM THE North LINE AND 660 FEET FROM
West LINE, SECTION 20 TOWNSHIP 13 S RANGE 38 E N.M.P.M.

5. Elevation (Show whether DF, RT, CR, etc.)
3829 GL

6. Indicate Type of Lease
State ☐ Fed. ☒

7. State Oil & Gas Lease No.

8. Well Agreement Name

9. Farm or Lease Name
Coy Lowe

10. Well No.
1

11. Field and Pool, or Wilocal
King Wolfcamp

12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

1. ☐ REMEDIAL WORK
2. ☐ PARTIALLY ABANDON
3. ☐ ALTER CASING
4. ☐ PLUG AND ABANDON
5. ☐ CHANGE PLANS
6. ☐ OTHER

SUBSEQUENT REPORT OF:

1. ☐ REMEDIAL WORK
2. ☐ COMMENCE DRILLING OPNS.
3. ☒ CASING TEST AND CEMENT JOB
4. ☐ ALTERING CASING
5. ☐ PLUG AND ABANDONMENT
6. ☐ OTHER

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed operations) SEE RULE 1103.

Spud at 7:45 a.m. on 10/12/88
13 3/8" -54.5# casing set @ 471'. Cemented with 500 sacks Cl "C" w/2% CaCl + 1/4# celocole.
Cement circulated to surface. Hole size 17 1/2". WOC 20 hours. (11 jts. of csg.)

On 10/19/88 ran 113 jts. 8 5/8" 24 & 32# 8rd K-55 & S-80 casing. DV tool @ 2966'. Set @ 4673'
Circulated. Cemented in 2 stages as follows: 1st stage w/730 sx 50/50 poz mix w/4% D-20, 1/4#
D-29 + 6# D-44. Tailed in w/250 sx Class "H" cement w/1% S-1. Plug down @ 10:30 p.m. 10/19/88
2 hours circulated thru DV tool @ 2966', 2 1/4 hours cement 2 nd stage w/1475 sx 35/65 poz mix w/
6% D-20 + 7# D-44 + 1% S-1. Plug down @ 5:00 a.m. 10/20/88. Cement circulated. Hole size 12 1/4
WOC 24 hours.

TD: 10,107'. Ran 263 jts. 5 1/2" 17# N-80 LT&C casing Set @ 10,107'. Cemented w/275 sx Cl. H
cement w/1/4# D-29 & .2% D-13. Plug down @ 4:00 a.m. 11/8/88. Hole size 7 7/8". TOC 9126'.

Log Tops: Rustler 2262' Wolfcamp LS 9392'
Yates 3100' XX Marker 9516'
San Andres 4559' 3 Brothers 9824'
Glorietta 6093' Bough A 9981'
Tubb 7371'
ABO 8043'

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signature: Brenda Coffman TITLE: Agent DATE: 1-24-89
ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR
Signature: _____ TITLE: _____ DATE: JAN 27 1989
Signature: _____ TITLE: _____ DATE: _____

RECEIVED

JAN 26 1989

CCD

HOBBS OFFICE