

WRS COMPLETION REPORTCOMPLETIONS SEC 35 TWP 13S RGE 37E
PI# 30-T-0014 10/26/90 30-025-30855-0000 PAGE 1NMEX LEA * 2250FSL 600FEL SEC NE SE
STATE COUNTY FOOTAGE SPOT
AMERICAN EXPL D DO
OPERATOR WELL CLASS INIT FIN
5 HOWARD FLEET
WELL NO. LEASE NAME
3861KB 3844GR KING
OPER ELEV FIELD/POOL/AREA
API 30-025-30855-0000LEASE NO. PERMIT OR WELL I.D. NO.
06/03/1990 08/12/1990 ROTARY VERT OIL
SPUD DATE COMP. DATE TYPE TOOL HOLE TYPE STATUS
11000 PNNSYLVN PATTERSON DRLG 5 RIG SUB 16
PROJ. DEPTH PROJ. FORM CONTRACTOR
DTD 10915 PB 10904 FM/TD PNNSYLVN
DRILLERS T.D. LOG T.D. PLUG BACK TO OLD T.D. FORM T.D.**LOCATION DESCRIPTION**

10 MI SE TATUM, NM

CASING/LINER DATACSG 13 3/8 @ 415 W/ 500 SACKS
CSG 8 5/8 @ 4525 W/ 1600 SACKS
CSG 5 1/2 @ 10915 W/ 1835 SACKS**TUBING DATA**

TBG 2 7/8 AT 10400

INITIAL POTENTIALIPP 129BOPD 150 MCFD 100BW 24HRS
PNNSYLVN PERF W/ 2/FT 10505-10874 GROSS
GTY 42.8 GOR 1163

TYPE	FORMATION	LTH	TOP	DEPTH/SUB	BSE	DEPTH/SUB
LOG	ANHYDRTE		2150	1694		
LOG	SALT		2345	1499	3144	700
LOG	SN ANDRS		4525	-681		
LOG	TUBB		7330	-3486		
LOG	ABO		8002	-4158		
LOG	PNNSYLVN		10500	-6656		

SUBSEA MEASUREMENTS FROM GR

CONTINUED IC# 300257013490

Copyrighted 1990
Reproduction
Prohibited**Petroleum Information**PI-WRS-C
Form No. 1**DB** a company of
The Dun & Bradstreet Corporation

COMPLETIONS SEC 35 TWP 13S RGE 37E
PI# 30-T-0014 10/26/90 30-025-30855-0000 PAGE 2

AMERICAN EXPL D DO
5 HOWARD FLEET

PRODUCTION TEST DATA

PNNSYLVN PERF W/ 2/FT 10505-10874 GROSS
PERF 10505-10582 10612-10673 10705-10729 10794-10824
PERF 10854-10856 10858-10866 10868-10874
ACID 10505-10729 4000GALS
15% NEFE
ACID 10794-10874 2000GALS
15% NEFE

LOGS AND SURVEYS /INTERVAL,TYPE/

LOGS	DLL	MLL	DENL
LOGS	GR	NEUT	ACSL

DRILLING PROGRESS DETAILS

AMERICAN EXPL
601 N LORAIN, STE 213
MIDLAND, TX 79701
915-687-0587
04/05 LOC/1990/
06/07 DRLG 1800
06/12 DRLG 4707
06/22 DRLG, NO DETAILS
06/28 DRLG 7344
07/05 DRLG 8390
07/12 DRLG 10015
07/19 10915 TD, WOCT
10/02 10915 TD, PB 10904, WOPT
10/23 RIG REL 07/15/90
10915 TD, PB 10904
COMP 8/12/90, IPP 129 BO, 150 MCFG, 100
BWP, GOR 1163, GTY 42.8
PROD ZONE - PENNSYLVANIAN 10505-10874
NO CORES OR DSTS RPTD